

# Non-Insulated (HR) Catalog

Wire Terminals / Hook

CATEGORY EDITION

# Non-Insulated (HR)

Wire Terminals / Hook / Non-Insulated (HR)



## Installation Information

Manufacturer	Tools	Color	Code
-			

#	Cat.No	Stud/Tab		Dimension (Inch)				Wire Range
		Size	A	B	C	D	H	A.W.G
1	TH1206	#6	0.768	0.146	0.374	0.039 (1.00)	0.142	12 - 10
2	TH1208	#8	0.768	0.169	0.374	0.039 (1.00)	0.142	12 - 10
3	TH1210	#10	0.768	0.209	0.374	0.039 (1.00)	0.142	12 - 10
4	TH1214	1/4	1.004	0.252	0.472	0.039 (1.00)	0.142	12 - 10
5	TH1238	3/8	1.091	0.413	0.591	0.039 (1.00)	0.142	12 - 10
6	TH1256	5/16	1.091	0.331	0.591	0.039 (1.00)	0.142	12 - 10
7	TH1604	#4	0.661	0.126	0.335	0.031 (0.80)	0.098	16 - 14
8	TH1608	#8	0.661	0.169	0.335	0.031 (0.80)	0.098	16 - 14
9	TH1610	#10	0.657	0.209	0.374	0.031 (0.80)	0.098	16 - 14
10	TH1614	1/4	0.858	0.252	0.472	0.031 (0.80)	0.098	16 - 14
11	TH1638	3/8	1.004	0.413	0.539	0.031 (0.80)	0.098	16 - 14
12	TH1656	5/16	0.858	0.331	0.472	0.031 (0.80)	0.098	16 - 14
13	TH2208	#8	0.622	0.169	0.315	0.030 (0.75)	0.075	22 - 16
14	TH2210	#10	0.622	0.209	0.315	0.030 (0.75)	0.075	22 - 16
15	TH2214	1/4	0.846	0.252	0.457	0.030 (0.75)	0.075	22 - 16
16	TH2238	3/8	1.004	0.413	0.539	0.030 (0.75)	0.075	22 - 16
17	TH2256	5/16	0.846	0.331	0.457	0.030 (0.75)	0.075	22 - 16