


750 kcmil Catalog

Compression Connectors / One hole 0°

CATEGORY EDITION

750 kcmil

Compression Connectors / One hole 0° / 750 kcmil



Installation Information

Manufacturer	Tools	Color	Code
T&B	TBM12 TBM14M	Black	106
Panduit	CT-920 CT-920CH	Black	P106
Burndy	Y35 Y45	Black	24

#	Cat.No	Wire Size			Dimension (in.)				
		Code	Flex Class G,H,I,K,M	Bolt Size	A	B	C	R	ID
1	DA7512	750kcmil	1325/24 = 535 kcmil	1/2	3.92	1.69	1.94	2.37	1.06
2	DA7512-251	750kcmil	777.7 kcmil 1925/24	5/8	3.74	1.38	2.17	2.50	1.17
3	DA7512-260	750kcmil	1325/24 = 535 kcmil	1/2	3.20	1.08	1.91	2.26	1.03
4	DA7512-261	750kcmil	777.7 kcmil 1925/24	5/8	3.43	1.08	2.19	2.49	1.17
5	DA7541-260	750kcmil	1325/24 = 535 kcmil	1 1/4	4.62	2.50	1.91	2.26	1.03
6	DA7558	750kcmil	1325/24 = 535 kcmil	5/8	3.81	1.58	1.94	2.37	1.06
7	DA7558-241	750kcmil	1325/24 = 646 kcmil	5/8	3.81	1.58	1.94	2.37	1.06
8	DA7558-250	750kcmil	1325/24 = 535 kcmil	5/8	4.52	1.94	1.89	2.72	1.03
9	DA7558-251	750kcmil	777.7 kcmil 1925/24	1/2	4.39	2.03	2.17	2.50	1.17
10	DA7558-260	750kcmil	1325/24 = 535 kcmil	5/8	3.45	1.33	1.91	2.26	1.03
11	DA7558-261	750kcmil	777.7 kcmil 1925/24	5/8	3.68	1.33	2.19	2.49	1.17
12	DA7578	750kcmil	1325/24 = 535 kcmil	7/8	4.11	1.88	1.94	2.37	1.06
13	DA7578-260	750kcmil	1325/24 = 535 kcmil	7/8	3.89	1.77	1.91	2.26	1.03
14	LA7512	750kcmil	1325/24 = 535 kcmil	1/2	4.35	1.25	1.94	3.24	1.06
15	LA7512-260	750kcmil	1325/24 = 535 kcmil	5/8	4.66	1.08	1.89	3.72	1.03
16	LA7512P-260	750kcmil	1325/24 = 535 kcmil	1/2	4.66	1.08	1.91	3.72	1.03
17	LA7538P-260	750kcmil	1325/24 = 535 kcmil	5/8	4.41	0.83	1.91	3.72	1.03
18	LA7558	750kcmil	1325/24 = 535 kcmil	5/8	4.68	1.58	1.94	3.24	1.06
19	LA7558-241	750kcmil	1325/24 = 535 kcmil	5/8	4.68	1.58	1.94	3.24	1.06
20	LA7558-250	750kcmil	1325/24 = 535 kcmil	3/8	5.52	1.94	1.89	3.72	1.03
21	LA7558-260	750kcmil	1325/24 = 535 kcmil	1/2	4.91	1.33	1.89	3.72	1.03
22	LA7578-250	750kcmil	1325/24 = 535 kcmil	1/2	5.61	2.03	1.89	3.72	1.03
23	WP7558-064	750kcmil	1325/24 = 535 kcmil	7/8	3.96	1.43	1.90	2.26	1.03