


250 kcmil Catalog

Compression Connectors / AL - Two hole 0°

CATEGORY EDITION

250 kcmil

Compression Connectors / AL - Two hole 0° / 250 kcmil



Installation Information

| Manufacturer | Tools | Color | Code |
|--------------|-----------------|-------|------|
| T&B | TBM8, TBM15BSCR | Red | 71 |
| Panduit | CT-720, CT-920 | Red | P71 |
| Burndy | Y39, Y45 | Red | 324 |

| # | Cat.No | Wire Size | | Dimension (in.) | | | | | | | |
|---|-------------|-----------|-----------|-----------------|------|------|------|------|------|------|------|
| | | Code | Bolt Size | A | B | C | D | F | G | ID | H |
| 1 | AL251243 | 250 kcmil | 1/2 | 5.53 | 3.00 | 1.29 | 0.27 | 0.50 | 1.75 | 0.65 | 1.93 |
| 2 | AL251243-52 | 250 kcmil | 1/2 | 5.78 | 3.38 | 1.25 | 0.31 | 0.63 | 1.75 | 0.59 | 1.80 |
| 3 | AL251243-62 | 250 kcmil | 1/2 | 5.16 | 3.11 | 1.26 | 0.33 | 0.63 | 1.75 | 0.59 | 1.45 |
| 4 | AL253801 | 250 kcmil | 3/8 | 4.46 | 1.93 | 1.29 | 0.27 | 0.38 | 1.00 | 0.65 | 1.93 |
| 5 | AL253801-62 | 250 kcmil | 3/8 | 3.94 | 1.89 | 1.26 | 0.33 | 0.44 | 1.00 | 0.59 | 1.45 |