

Hook Catalog

Wire Terminals

CATEGORY EDITION

Table of Contents

Catalog structure and section page index

Non-Insulated (HR)	3
Viny-Insulated (VHR)	5
Nylon-Insulated (AEHR)	7

Non-Insulated (HR)

Wire Terminals / Hook

Non-Insulated (HR)

Wire Terminals / Hook / Non-Insulated (HR)



Installation Information

Manufacturer	Tools	Color	Code
-			

#	Cat.No	Stud/Tab		Dimension (Inch)				Wire Range
		Size	A	B	C	D	H	A.W.G
1	TH1206	#6	0.768	0.146	0.374	0.039 (1.00)	0.142	12 - 10
2	TH1208	#8	0.768	0.169	0.374	0.039 (1.00)	0.142	12 - 10
3	TH1210	#10	0.768	0.209	0.374	0.039 (1.00)	0.142	12 - 10
4	TH1214	1/4	1.004	0.252	0.472	0.039 (1.00)	0.142	12 - 10
5	TH1238	3/8	1.091	0.413	0.591	0.039 (1.00)	0.142	12 - 10
6	TH1256	5/16	1.091	0.331	0.591	0.039 (1.00)	0.142	12 - 10
7	TH1604	#4	0.661	0.126	0.335	0.031 (0.80)	0.098	16 - 14
8	TH1608	#8	0.661	0.169	0.335	0.031 (0.80)	0.098	16 - 14
9	TH1610	#10	0.657	0.209	0.374	0.031 (0.80)	0.098	16 - 14
10	TH1614	1/4	0.858	0.252	0.472	0.031 (0.80)	0.098	16 - 14
11	TH1638	3/8	1.004	0.413	0.539	0.031 (0.80)	0.098	16 - 14
12	TH1656	5/16	0.858	0.331	0.472	0.031 (0.80)	0.098	16 - 14
13	TH2208	#8	0.622	0.169	0.315	0.030 (0.75)	0.075	22 - 16
14	TH2210	#10	0.622	0.209	0.315	0.030 (0.75)	0.075	22 - 16
15	TH2214	1/4	0.846	0.252	0.457	0.030 (0.75)	0.075	22 - 16
16	TH2238	3/8	1.004	0.413	0.539	0.030 (0.75)	0.075	22 - 16
17	TH2256	5/16	0.846	0.331	0.457	0.030 (0.75)	0.075	22 - 16

Viny-Insulated (VHR)

Wire Terminals / Hook

Viny-Insulated (VHR)

Wire Terminals / Hook / Viny-Insulated (VHR)



Installation Information

Manufacturer	Tools	Color	Code
-			

#	Cat.No	Stud/Tab		Dimension (Inch)				Wire Range
		Size	A	B	C	D		
1	TH1204V	#4	1.051	0.126	0.374	0.039 (1.00)	12 - 10	
2	TH1206V	#6	1.051	0.146	0.374	0.039 (1.00)	12 - 10	
3	TH1208V	#8	1.051	0.169	0.374	0.039 (1.00)	12 - 10	
4	TH1210V	#10	1.051	0.209	0.374	0.039 (1.00)	12 - 10	
5	TH1214V	1/4	1.287	0.252	0.472	0.039 (1.00)	12 - 10	
6	TH1238V	3/8	1.374	0.413	0.591	0.039 (1.00)	12 - 10	
7	TH1256V	5/16	1.374	0.331	0.591	0.039 (1.00)	12 - 10	
8	TH1604V	#4	0.906	0.126	0.335	0.031 (0.80)	16 - 14	
9	TH1608V	#8	0.906	0.169	0.335	0.031 (0.80)	16 - 14	
10	TH1610V	#10	0.906	0.209	0.374	0.031 (0.80)	16 - 14	
11	TH1614V	1/4	1.106	0.252	0.472	0.031 (0.80)	16 - 14	
12	TH1638V	3/8	1.256	0.413	0.535	0.031 (0.80)	16 - 14	
13	TH1656V	5/16	1.106	0.331	0.472	0.031 (0.80)	16 - 14	
14	TH2208V	#8	0.854	0.169	0.315	0.030 (0.75)	22 - 16	
15	TH2210V	#10	0.854	0.209	0.315	0.030 (0.75)	22 - 16	
16	TH2214V	1/4	1.087	0.252	0.457	0.030 (0.75)	22 - 16	
17	TH2238V	3/8	1.24	0.413	0.539	0.030 (0.75)	22 - 16	
18	TH2256V	5/16	1.087	0.331	0.457	0.030 (0.75)	22 - 16	

Nylon-Insulated (AEHR)

Wire Terminals / Hook

Nylon-Insulated (AEHR)

Wire Terminals / Hook / Nylon-Insulated (AEHR)



Installation Information

Manufacturer	Tools	Color	Code
-			

#	Cat.No	Stud/Tab		Dimension (Inch)				Wire Range
		Size	A	B	C	D		
1	TH1204N	#4	1.051	0.126	0.374	0.039 (1.00)	12 - 10	
2	TH1206N	#6	1.051	0.146	0.374	0.039 (1.00)	12 - 10	
3	TH1208N	#8	1.051	0.169	0.374	0.039 (1.00)	12 - 10	
4	TH1210N	#10	1.051	0.209	0.374	0.039 (1.00)	12 - 10	
5	TH1214N	1/4	1.287	0.252	0.472	0.039 (1.00)	12 - 10	
6	TH1238N	3/8	1.374	0.413	0.591	0.039 (1.00)	12 - 10	
7	TH1256N	5/16	1.374	0.331	0.591	0.039 (1.00)	12 - 10	
8	TH1604N	#4	0.906	0.126	0.335	0.031 (0.80)	16 - 14	
9	TH1608N	#8	0.906	0.169	0.335	0.031 (0.80)	16 - 14	
10	TH1610N	#10	0.906	0.209	0.374	0.031 (0.80)	16 - 14	
11	TH1614N	1/4	1.106	0.252	0.472	0.031 (0.80)	16 - 14	
12	TH1638N	3/8	1.256	0.413	0.539	0.031 (0.80)	16 - 14	
13	TH1656N	5/16	1.106	0.331	0.472	0.031 (0.80)	16 - 14	
14	TH2208N	#8	0.854	0.169	0.315	0.030 (0.75)	22 - 16	
15	TH2210N	#10	0.854	0.209	0.315	0.030 (0.75)	22 - 16	
16	TH2214N	1/4	1.087	0.252	0.457	0.030 (0.75)	22 - 16	
17	TH2238N	3/8	1.24	0.413	0.539	0.030 (0.75)	22 - 16	
18	TH2256N	5/16	1.087	0.331	0.457	0.030 (0.75)	22 - 16	