


Nylon-Insulated (AER) Catalog

Wire Terminals / Ring

CATEGORY EDITION

Nylon-Insulated (AER)

Wire Terminals / Ring / Nylon-Insulated (AER)




Installation Information

Manufacturer	Tools	Color	Code
-			

#	Cat.No	Stud/Tab		Dimension (Inch)			Wire Range	
		Size	A	B	C	D	A.W.G	A.W.G
1	TR1204N	#4	1.051	0.126	0.374	0.039 (1.00)	12 - 10	12 - 10
2	TR1206N	#6	1.051	0.146	0.374	0.039 (1.00)	12 - 10	12 - 10
3	TR1208N	#8	1.051	0.169	0.374	0.039 (1.00)	12 - 10	12 - 10
4	TR1208NS	#8	1.051	0.169	0.291	0.039 (1.00)	12 - 10	12 - 10
5	TR1210N	#10	1.051	0.209	0.374	0.039 (1.00)	12 - 10	12 - 10
6	TR1210NS	#10	1.051	0.209	0.291	0.039 (1.00)	12 - 10	12 - 10
7	TR1212	1/2	1.559	0.512	0.756	0.039 (1.00)	12 - 10	12 - 10
8	TR1214N	1/4	1.287	0.252	0.472	0.039 (1.00)	12 - 10	12 - 10
9	TR1238N	3/8	1.374	0.413	0.591	0.039 (1.00)	12 - 10	12 - 10
10	TR1256N	5/16	1.374	0.331	0.591	0.039 (1.00)	12 - 10	12 - 10
11	TR1604N	#4	0.906	0.126	0.335	0.031 (0.80)	16 - 14	16 - 14
12	TR1604NM	#4	0.811	0.126	0.26	0.031 (0.80)	16 - 14	16 - 14
13	TR1606N	#6	0.811	0.146	0.26	0.031 (0.80)	16 - 14	16 - 14
14	TR1606NL	#6	0.906	0.146	0.335	0.031 (0.80)	16 - 14	16 - 14
15	TR1608N	#8	0.906	0.169	0.335	0.031 (0.80)	16 - 14	16 - 14
16	TR1608NM	#8	0.819	0.169	0.26	0.031 (0.80)	16 - 14	16 - 14
17	TR1610N	#10	0.906	0.209	0.374	0.031 (0.80)	16 - 14	16 - 14
18	TR1610NM	#10	0.906	0.209	0.335	0.031 (0.80)	16 - 14	16 - 14
19	TR1612	1/2	1.398	0.512	0.748	0.031 (0.80)	16 - 14	16 - 14
20	TR1614N	1/4	1.106	0.252	0.472	0.031 (0.80)	16 - 14	16 - 14
21	TR1638N	3/8	1.256	0.413	0.539	0.031 (0.80)	16 - 14	16 - 14
22	TR1656N	5/16	1.106	0.331	0.472	0.031 (0.80)	16 - 14	16 - 14
23	TR2204N	#4	0.689	0.126	0.217	0.030 (0.75)	22 - 16	22 - 16
24	TR2206N	#6	0.689	0.146	0.217	0.030 (0.75)	22 - 16	22 - 16
25	TR2206NM	#6	0.803	0.146	0.26	0.030 (0.75)	22 - 16	22 - 16
26	TR2208N	#8	0.854	0.169	0.315	0.030 (0.75)	22 - 16	22 - 16
27	TR2208NM	#8	0.803	0.169	0.26	0.030 (0.75)	22 - 16	22 - 16
28	TR2210N	#10	0.854	0.209	0.315	0.030 (0.75)	22 - 16	22 - 16
29	TR2212N	1/2	1.378	0.512	0.748	0.030 (0.75)	22 - 16	22 - 16
30	TR2214N	1/4	1.087	0.252	0.457	0.030 (0.75)	22 - 16	22 - 16

Nylon-Insulated (AER)

Wire Terminals / Ring / Nylon-Insulated (AER)



Installation Information

Manufacturer	Tools	Color	Code
-			

#	Cat.No	Stud/Tab	Dimension (Inch)				Wire Range	
		Size	A	B	C	D	A.W.G	A.W.G
31	TR2238N	3/8	1.24	0.413	0.539	0.030 (0.75)	22 - 16	22 - 16
32	TR2256N	5/16	1.087	0.331	0.457	0.030 (0.75)	22 - 16	22 - 16