

2/0 AWG Catalog

Compression Connectors / One hole 45°

CATEGORY EDITION

2/0 AWG

Compression Connectors / One hole 45° / 2/0 AWG



Installation Information

Manufacturer	Tools	Color	Code
T&B	TBM5 TBM8	Black	45
Panduit	CT-720 CT-920	Black	P45
Burndy	MY29 Y644M	Black	13

#	Cat.No	Wire Size			Dimension (in.)				
		Code	Flex Class G,H,I,K,M	Bolt Size	B	C	D	H	
1	DA2010F-251	2/0 AWG	325/24 2/0 Weld	#10	0.54	0.96	0.13	0.51	
2	DA2010F-261	2/0 AWG	325/24 2/0 Weld	#10	0.52	0.93	0.13	0.50	
3	DA2012F	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	1/2	1.25	0.83	0.13	0.44	
4	DA2012F-250	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	1/2	1.09	0.85	0.13	0.45	
5	DA2012F-251	2/0 AWG	325/24 2/0 Weld	1/2	1.09	0.96	0.13	0.51	
6	DA2012F-252	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	1/2	1.09	0.85	0.13	0.45	
7	DA2012F-260	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	1/2	1.08	0.83	0.12	0.44	
8	DA2012F-261	2/0 AWG	325/24 2/0 Weld	1/2	1.08	0.93	0.13	0.50	
9	DA2014F	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	1/4	0.65	0.83	0.13	0.44	
10	DA2014F-250	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	1/4	0.78	0.85	0.13	0.45	
11	DA2014F-251	2/0 AWG	325/24 2/0 Weld	1/4	0.78	0.96	0.13	0.51	
12	DA2014F-252	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	1/4	0.78	0.85	0.13	0.45	
13	DA2014F-260	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	1/4	0.64	0.83	0.12	0.44	
14	DA2014F-261	2/0 AWG	325/24 2/0 Weld	1/4	0.64	0.93	0.13	0.50	
15	DA2034F-250	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	3/4	1.69	1.06	0.10	0.45	
16	DA2034F-251	2/0 AWG	325/24 2/0 Weld	3/4	1.52	0.96	0.13	0.51	
17	DA2034F-260	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	3/4	1.52	0.96	0.12	0.44	
18	DA2034F-261	2/0 AWG	325/24 2/0 Weld	3/4	1.52	1.10	0.11	0.50	
19	DA2038F	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	3/8	0.93	0.83	0.13	0.44	
20	DA2038F-250	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	3/8	0.84	0.85	0.13	0.45	
21	DA2038F-251	2/0 AWG	325/24 2/0 Weld	3/8	0.84	0.96	0.13	0.51	
22	DA2038F-252	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	3/8	0.84	0.85	0.13	0.45	
23	DA2038F-260	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	3/8	0.83	0.83	0.12	0.44	
24	DA2038F-261	2/0 AWG	325/24 2/0 Weld	3/8	0.83	0.93	0.13	0.50	
25	DA2056F	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	5/16	0.88	0.83	0.13	0.44	
26	DA2056F-250	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	5/16	0.78	0.85	0.13	0.45	
27	DA2056F-251	2/0 AWG	325/24 2/0 Weld	5/16	0.78	0.96	0.13	0.51	
28	DA2056F-260	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	5/16	0.70	0.83	0.12	0.44	
29	DA2056F-261	2/0 AWG	325/24 2/0 Weld	5/16	0.70	0.93	0.13	0.50	
30	DA2058F-251	2/0 AWG	325/24 2/0 Weld	5/8	1.33	0.96	0.13	0.51	

2/0 AWG

Compression Connectors / One hole 45° / 2/0 AWG



Installation Information

Manufacturer	Tools	Color	Code
T&B	TBM5 TBM8	Black	45
Panduit	CT-720 CT-920	Black	P45
Burndy	MY29 Y644M	Black	13

#	Cat.No	Wire Size			Dimension (in.)				
		Code	Flex Class G,H,I,K,M	Bolt Size	B	C	D	H	
31	DA2058F-260	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	5/8	1.33	0.88	0.11	0.44	
32	DA2058F-261	2/0 AWG	325/24 2/0 Weld	5/8	1.33	0.93	0.13	0.50	
33	DDA2056F-252	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	5/16	0.78	0.85	0.13	0.45	
34	LA2012F	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	1/2	1.25	0.83	0.13	0.44	
35	LA2012F-250	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	1/2	1.06	0.85	0.13	0.45	
36	LA2012F-260	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	1/2	1.08	0.83	0.12	0.44	
37	LA2012FP-251	2/0 AWG	325/24 2/0 Weld	1/2	1.09	0.96	0.13	0.51	
38	LA2012FP-260	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	1/2	1.08	0.83	0.12	0.44	
39	LA2012FP-261	2/0 AWG	325/24 2/0 Weld	1/2	1.08	0.93	0.13	0.50	
40	LA2014FP-251	2/0 AWG	325/24 2/0 Weld	1/4	0.78	0.96	0.13	0.51	
41	LA2014FP-260	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	1/4	0.64	0.83	0.12	0.44	
42	LA2014FP-261	2/0 AWG	325/24 2/0 Weld	1/4	0.64	0.93	0.13	0.50	
43	LA2038F	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	3/8	0.93	0.83	0.13	0.44	
44	LA2038F-250	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	3/8	0.84	0.85	0.13	0.45	
45	LA2038F-260	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	3/8	0.83	0.83	0.12	0.44	
46	LA2038FP-251	2/0 AWG	325/24 2/0 Weld	3/8	0.84	0.96	0.13	0.51	
47	LA2038FP-260	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	3/8	0.83	0.83	0.12	0.44	
48	LA2038FP-261	2/0 AWG	325/24 2/0 Weld	3/8	0.83	0.93	0.13	0.50	
49	WP2038F-011	2/0 AWG	125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	3/8	0.81	0.83	0.12	0.44	