

700 kcmil Catalog

Compression Connectors / One hole 45°

CATEGORY EDITION

700 kcmil

Compression Connectors / One hole 45° / 700 kcmil



Installation Information

Manufacturer	Tools	Color	Code
T&B	40TON TBM8-750	Pink	99
Panduit	-	Pink	-
Burndy	Y39 Y644M	Pink	400

#	Cat.No	Wire Size		Dimension (in.)				
		Code	Flex Class G,H,I,K,M	Bolt Size	B	C	D	H
1	DA7112F-241	700 kcmil	1325/24 = 535 kcmil 427/.0342	1/2	1.69	1.81	0.28	0.97
2	DA7158F	700 kcmil	1325/24 = 535 kcmil 427/.0342	5/8	1.58	1.84	0.23	0.97
3	DA7158F-241	700 kcmil	1325/24 = 535 kcmil 427/.0342	5/8	1.58	1.81	0.28	0.97
4	DA7158F-260	700 kcmil	1325/24 = 535 kcmil 427/.0342	5/8	1.33	1.84	0.27	0.97
5	DA7512F-260	750 kcmil	1325/24 = 535 kcmil	1/2	1.08	1.91	0.27	1.03
6	DA7541F-260	750 kcmil	1325/24 = 535 kcmil	1 1/4	2.50	1.91	0.27	1.03
7	DA7558F	750 kcmil	1325/24 = 535 kcmil	5/8	1.58	1.94	0.27	1.06
8	DA7558F-241	750 kcmil	1600/24 = 646 kcmil	5/8	1.58	1.94	0.27	1.06
9	DA7558F-260	750 kcmil	1325/24 = 535 kcmil	5/8	1.33	1.91	0.27	1.03
10	DA7578F-260	750 kcmil	1325/24 = 535 kcmil	7/8	1.77	1.91	0.27	1.03
11	LA7512F	750 kcmil	1325/24 = 535 kcmil	1/2	1.25	1.94	0.27	1.06
12	LA7512F-260	750 kcmil	1325/24 = 535 kcmil	1/2	1.08	1.89	0.27	1.03
13	LA7512FP-260	750 kcmil	1325/24 = 535 kcmil	1/2	1.08	1.91	0.27	1.03
14	LA7538FP-260	750 kcmil	1325/24 = 535 kcmil	3/8	0.83	1.91	0.27	1.03
15	LA7558F	750 kcmil	1325/24 = 535 kcmil	5/8	1.58	1.94	0.27	1.06
16	LA7558F-241	750 kcmil	1600/24 = 646 kcmil	5/8	1.58	1.94	0.27	1.06
17	LA7558F-260	750 kcmil	1325/24 = 535 kcmil	5/8	1.33	1.89	0.27	1.03
18	WP7112F-089	700 kcmil	1325/24 = 535 kcmil 427/.0342	1/2	1.69	1.79	0.27	0.95
19	WP7158F-039	700 kcmil	1325/24 = 535 kcmil 427/.0342	5/8	1.69	1.79	0.27	0.95
20	WP7558F-071	750 kcmil	1325/24 = 535 kcmil	5/8	1.43	1.90	0.27	1.03