		4 EINFORMATION ON THIS DRAWING IS THE PROERTY OF CELESTRA, IS		3		2								,			
	DISCL	OSED IN CON	NFIDENCE ANI	NOT TO BE					CELESTRA CAT.NO	CODE	SIZE	BOLT SIZE	B MIN	C ±0.04	D ±0.015	H ±0.01	
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.						0022	150 Navy 2/0 Weld						i
									DA3056F	3/0 AWG	325/24 = 131 kcmil 133/.0316	5/16	0.88	0.92	0.13	0.51	
_											259/.0227	2, 12					_
D	N	OTE:	1. ALL	DIMENSION	IS ARE IN II	NCHES UNLESS	S OTHERWISE	l			427/.0177						D
				CIFIED.													
						S AND J SERIES	OF CAT.NO.S	ARE									
						X/24 STRANDE											
	1		PRE	FIX CAT.NO	D.WITH "L" I	HAS NOT PEEP	HOLE UNLESS			H	BOLT SI	ZE					
				IERWISE SF H "P".	ECIFIED IN	THE SUFFIX O	F THE CAT.NO.										
	I	IATERIAL:				UGHT COPPER)			H(V)) (V)	c c						
_		INISH:				SS OTHERWIS											_
С	"	IINISH.	SPE	CIFED PLAT	TE PER MIL	- T -16366.	C			F							С
			SUF	FIX CAT.NO	.WITH "SP"	FOR SILVER.				L	•						
_		INSTALLATION GUIDE							Color coded barrel markings								_
	D	DIE CODE = 50							Wire inspection hole								
	٥ ا	IE COLOR =	= Orange						45,	V.	vire inspection no	ie					
											+						
_									<u>, </u>		<u> </u>			4	_		_
В		-		V							D						В
		c (VL) US	RoHS 2002/95/EC						[∟] Beveled wi	re entry						
		WIR ZM	LISTED RE CONNECTORS VV/2/7/8.E513813		,												
											® CELES	TRA	CO	RPO	RATIO	NC	
٨										76. Huancun Rd. Zhongcun Town.						n.	
									<u> </u>	www.huyaco.coi							,
Α										WIRE CONNECTORS AND SOLDERING							A
										LUGS FOR CODE AND FLEX CABLE							
	00	01-Dec-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.						d.	WROUGHT COPPER DA3056F NTS							ROJECTION	1
ı	REV	DATE	DWN	CHK		DESCR	PTION		ECN F	ELECTRO TIN PLATE	DWG. NO. 186-cp10	43	init In	СН	⊕ €] ,
			4				3	4		2				1			
					•							•					