			4				3		7	2				1			_
'					PROERTY OF C				CELESTRA CAT.NO			BOLT SIZE	B MIN	C	D .015	H	'
			FOR WHICH					-	CAT.NO	CODE	FLEX 150 Navy 2/0 Weld		IVIIN	±0.04	±0.015	±0.01	-
											325/24 = 131 kcmil						
									DA3038F	3/0 AWG	133/.0316 259/.0227	3/8	0.93	0.92	0.13	0.51	
D											427/.0177						D
	N	IOTE:		DIMENSION CIFIED.	IS ARE IN INC	CHES UNLESS	OTHERWISE										
						SERIES OF CA	AT NO S ARE										
			LIST	ED BY "UNI	DERWRITERS	INC." AND "C	SA" FOR USE										
			ON	CODE WIRE	S AND FLEX/2	24 STRANDEI	O CABLES.				DOLT OF	7 -					l
							HOLE UNLESS			H 	BOLT SIZ	<u>Z</u> E					
				IERWISE SF H "P".	ECIFIED IN T	HE SUFFIX O	F THE CAT.NO.										
	 	MATERIAL:				GHT COPPER	•			Huya ()						
		INISH:				S OTHERWIS			,		<u> </u>						
С	「	IIVION.	SPE	CIFED PLAT	E PER MIL -	T -16366.	E			'							С
			SUF	FIX CAT.NO	.WITH "SP" F	OR SILVER.					3 -						
									λ.	C	olor coded barrel	markir	าตร				
\rightarrow		NSTALLATIO							2		nor coded barrer	manni	igo				\leftarrow
		DIE COLOR :							45° ±3°	Vie copp.	Vire inspection ho	le					
									4		1			ľ			
									<u> </u>								
В					V						Ť				_		В
			c(y	L)US	RoHS	i.				\	D						
			1181	ren .	2002/95/EC					[∟] Beveled wi	re entry						
			WIRE CONI	ECTORS E513913													
	1																-
											R CELES	TRA	CO	RPOI	RATIO)N	1
										HUYA	76. Hua						
										www.huyaco.com	n Panyu [Dist. G	uangz	hou 5	11495.		
Α			 						TI	WIRE CONNECTORS AND SOLDERING A] A
		LUGS FOR CODE AND FLEX CABL															
									MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECT							OJECTION	-
			Ruby Feng	-	Ce		rds Spec. Initialed			WROUGHT COPPER	DA3038F		N.	TS _	фг	7	
1	REV	DATE	DWN	CHK	1	DESCRI		A	ECN F	ELECTRO TIN PLATE	186-cp10	44 "	IN	ICH	\$ L]
			4				3	4	7	2				1			
								'									