	_													
		4		3	\bigvee		2				1			
I			HE PROERTY OF CELESTRA, BE REPRODUCED, USED OR	IS		CELESTRA	WIRE		BOLT	В	С	D	Н	'
		T FOR WHICH FURNISHE				CAT.NO	CODE	FLEX	SIZE	MIN		±0.015		
					<u> </u>	DA3010F-251	3/0 AWG	450/24 3/0 Weld	#10	0.54	1.06	0.14	0.57	
D														D
	NOTE:	_	ONS ARE IN INCHES UN	LESS OTHERWISE										
		SPECIFIED.				Ц		/-BOLT SIZ	7F					
			.,LB,WP AND J SERIES (NDERWRITERS INC." AN											
			RES AND FLEX/24 STRA											
_	1	PRF-FIX CAT.	NO.WITH "I " HAS NOT F	PEEP HOLE UNLESS			Huya Huya	· c						
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.													
		WITH "P". MATERIAL: LUCU CONDUCTIVITY MEDICUT CORRER												
	MATERIAL:	HIGH CONDU	CTIVITY WROUGHT CO	PPER			L-B							
С	FINISH:		PLATE UNLESS OTHER											С
			ATE PER MIL - T -16366. IO.WITH "SP" FOR SILVI		Color coded barrel markings									
								ioi coded barrer	IIIai Kii	iys				
						45,43,	W	ire inspection ho	le					
_	INSTALLATION GUIDE													_
	DIE CODE =	= 50				1								
	DIE COLOR	= Orange						A						
								D						
		_					ackslash Beveled wire	e entry						
В			✓											В
		CCLOUS	RoHS											
		LISTED												
		WIRE CONNECTORS ZMVV/2/7/8.E513813												
_	1													_
								R CELES	TDA	<u></u>	DDOI	DATIO)NI	
							HUYA	76. Hua						
	-						www.huyaco.com	_						
Α						TITL	E MIDE CON		V V I D		DEF			Α
								INECTORS						
							LUGS FOR	R CODE AND) FLI	EX C	ABL	L		
	00 23-Aug-25	Ruby Feng Sinia Qi	Celestra St	andards Spec. Initialed	d.	MAT	ERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	PRT. NO. DA3010F-251	S	CALE N	TS THE	RID ANGLE PF	OJECTION	
	REV DATE	DWN CHK	DES	SCRIPTION		ECN FINIS		DWG. NO. 186-cp10	54 UI	NIIT	ICH -	(E	\exists	
		4		3	\triangle	· · ·	2	<u> </u>	1		1			•
	-		ı		\top				ı					