			4				3		7	2				1			_
'				AWING IS THE D NOT TO BE		CELESTRA, IS			CELESTRA	•	SIZE	BOLT	В	С	D 015	Н	'
			FOR WHICH			D, 002B 011			CAT.NO	CODE	FLEX 150 Navy 2/0 Weld	SIZE	MIN	±0.04	±0.015	±0.01	
											325/24 = 131 kcmil						
									LA3012F-25	50 3/0 AWG	133/.0316 259/.0227	1/2	1.09	0.96	0.13	0.51	
D											427/.0177						D
	N	OTE:		DIMENSION CIFIED.	IS ARE IN II	NCHES UNLESS	OTHERWISE										
						CAND LEEDIES	OF CAT.NO.S ARE										
			LIS	TED BY "UNI	DERWRITE	RS INC." AND "C	SA" FOR USE										
			ON	CODE WIRE	S AND FLE	X/24 STRANDEI	D CABLES.				—DOLT 01	7 -					
							HOLE UNLESS			H 	BOLT SIZ	<u>Z</u> E					
				HERWISE SF "H "P".	ECIFIED IN	THE SUFFIX O	F THE CAT.NO.										
	M.	ATERIAL:	HIG	H CONDUCT	TIVITY WRO	UGHT COPPER	8			Huya Huya	Ç						
_	l	NISH:				SS OTHERWIS					<u> </u>						
С	l ''	INIOI I.	SPE	CIFED PLAT	E PER MIL	- T -16366.	_				} -						С
			SUF	FIX CAT.NC	.WITH "SP"	FOR SILVER.				-)						
									>		olor coded barrel	markir	ngs	1			
\rightarrow		ISTALLATIC IE CODE = :							ů/				ŭ				\leftarrow
		IE COLOR =							45.43.	Die Con-	Vire inspection ho	le			4		
											↓						
									<u> </u>								
В				,							Ţ			ı			В
	CUL) US ROHS, Beveled wire entry								re entry								
		1	ISTER	2002/95/EC						Develed Wi	re entry						
		WIR ZM	E CONNECTORS VV/2/7/8.E513913														
																	l
	L																
										HUYA	® CELES	TRA	CO	RPOI	RATIO	NC	
																n.	
										www.huyaco.co	m Panyu [JIST. G	uangz	nou 5	11495.		,
Α			TITLE WIRE CONNECTORS AND SOLDERIN							RING		Α					
		LUGS FOR CODE AND FLEX CABLE							Е								
	00	14-Dec-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.						MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTION NTS NTS							OJECTION		
	REV	DATE	DWN	СНК		DESCRI	PTION		ECN F	INISH ELECTRO TIN PLATE	DWG. NO. 186-cp10	71 ^U	NIIT	iCH -	(E	\exists	
			4				3	Δ		2		i		1			'
					ı			T				'					