								I									
		4 3			2			1					_				
'					PROERTY OF CELE REPRODUCED, USE				CELESTRA CAT.NO			BOLT SIZE	B MIN	C .0.04	D 015	H	'
			FOR WHICH					ŀ	CAT.NO	CODE	FLEX 200 Navy 3/0 Weld	SIZE	IVIIIN	±0.04	±0.015	±0.01	ł
									DA4014F-26	60 4/0 AWG	450/24 = 182 kcmil	1/4	0.64	1.02	0.14	0.56	
								l			703/.0154						1
D																	D
	N	IOTE:		DIMENSION CIFIED.	IS ARE IN INCHE	ES UNLESS	OTHERWISE										
			2 All	DADBIAL	B WP AND J SEF	RIES OF CA	T NO S ARE										
		 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. 							H BOLT SIZE								
																	
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.							exp. C								
				H "P".	COIFIED IN THE	SUFFIX OF	THE CATINO.		-	THE Y	C						
	М	IATERIAL:	HIGI	H CONDUCT	TIVITY WROUGH	IT COPPER											
_	F	INISH:	FLF	CTOR-TIN P	LATE UNLESS C	OTHERWISE	=			⊸ -B	3 -						
С			SPE	CIFED PLAT	TE PER MIL - T -1	16366.											С
			SUF	FIX CAT.NO).WITH "SP" FOR	SILVER.											
									<u> </u>	Cc	olor coded barrel	markir	ıgs	\leftarrow	_		
_										Alira inapaction hala							
\rightarrow		NSTALLATION NE CODE =							45° ±3°	V Cite	lire inspection ho	le			4		\leftarrow
	D	IE COLOR :	= Purple								V						
									<u>†</u>					Ļ			
											D						
В					V					_Beveled wir	re entry						В
			C	L)U S	RoHS 2002/95/EC						,						
			LIST	TED													
			WIRE CONF	ECTORS E513913													
										1 1 1 1 3 / A	(R) CELES	TRA	COI	RPO	RATIO	ON	
										HUYA						n.	
_									 	www.huyaco.cor	m Panyu [Dist. G	uangz	hou 5	11495.		A
Α		TITLE WIRE CONNECTORS A					AND	ND SOLDERING									
		LUGS FOR CODE AND FLEX															
	00	00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.							MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECT								1
	REV	DATE	DWN	CHK	- Celes	DESCRIF		•	ECN FI	NISH ELECTRO TIN PLATE	DA4014F-260 DWG. NO. 186-cp10	R6 UI	NIT	ICH .	() E	\Box	
	1 \ L V		4	0/110	<u> </u>	22001(11	3	<u></u>		2	100-0010	 	IIN	1 T	¥	_	1
			7		I		5	4	7	2		I		'			