		4				3	\neg	7	2				1			
I		THE INFORMATION ON THIS DRAWING IS THE PROERTY OF CELESTRA, IS DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR				CELESTRA			BOLT	В	С	D	Н			
	DISLOSED EXCEP			EPRODUCED, US	DED OR			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.01	
								LA4012F-260	60 4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	1/2	1.08	1.02	0.14	0.56	
D																D
_	NOTE:		DIMENSIONS	S ARE IN INCH	ES UNLES	S OTHERWISE										_
		LIST	ED BY "UND	WP AND J SE ERWRITERS II AND FLEX/24	NC." AND "C	CSA" FOR USE		HBOLT SIZE								
		OTH				P HOLE UNLESS OF THE CAT.NO.		exin H C								
	MATERIAL:	HIGI	H CONDUCT	VITY WROUGI	НТ СОРРЕР	2										
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.										С					
\rightarrow	INSTALLATION GUIDE DIE CODE = 54 DIE COLOR = Purple							Color coded barrel markings								\leftarrow
В									Beveled win	D re entry						В
		ZM√V/2/7/8	E513913													_
								1 1	HUYA		ncun	Rd. Zh	nongci	un Tow	n.	
A									WIRE CONNECTORS AND SOLDERING							
	00 00 000	Duby Dar -		0-1-	otro Otarada	vide Creatively		MA	ATERIAL HIGH-CONDUCTIVITY	PRT. NO.		CALE	THE		ROJECTION	
	00 23-Aug-25 REV DATE	Ruby Feng	CHK	Cele	DESCR	ards Spec. Initiale	;u.		WROUGHT COPPER	LA4012F-260 DWG. NO. 186-cp11	17 U	NT IN		Ð E	\square	
		4			DLOON	3	\wedge		ELECTRO TIN PLATE	100-cp11		IN	СН 1	Υ ⁻	7	I
		-+		I		0	4		2		I		1			