			4		I		3		7	2			1		
I	DISCL	OSED IN CON		D NOT TO BE F	PROERTY OF CELES REPRODUCED, USE			*	CELESTRA CAT.NO	A WIRE CODE	FLEX S	OLT B SIZE MIN		D H 0.015 ±0.0	_
								l	LA6138FP-2	260 600 kcmil	-	3/8 0.83	1.74	0.26 0.93	3
D	D NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.														
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.							H BOLT SIZE						
PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".															
	M	IATERIAL:	HIGI	H CONDUCT		COPPER				B					
С	F	INISH:	ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.)	С		
\rightarrow	INSTALLATION GUIDE DIE CODE = 94 DIE COLOR = Green)	\downarrow		
В	B COULS ROLLS														в
	WIRE CONNECTORS ZMVV/27/8LE513B13													_	
										HUYA		RA CO cun Rd. Zh st. Guangz	nongcun	n Town.	
A									TITLE WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE						A
	00	23-Aug-25	Ruby Feng	Sinia Qiu	Celesi	tra Standard	s Spec. Initialed	d.	М	ATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	PRT. NO. LA6138FP-260	SCALE N	TS THRID	ANGLE PROJECTI	ИС
I	REV	DATE	DWN	СНК		DESCRIP			ECN FI	ELECTRO TIN PLATE	DWG. NO. 186-cp1279	UNIT	існ €		
			4				3	4	7	2			1		