					1								\equiv
		4		3	\bigvee	2				1			
ı		ON THIS DRAWING IS THE F IFIDENCE AND NOT TO BE R			CELESTR			BOLT	В	С	D	Н	
		FOR WHICH FURNISHED.	ET NODOGED, GGED GN		CAT.NO		FLEX 1325/24 = 535	SIZE	MIN	±0.04	±0.015	±0.01	
					DA7158F	700 kcmil	kcmil 427/.0342	5/8	1.58	1.84	0.23	0.97	
D													D
	NOTE:	ALL DIMENSIONS SPECIFIED.	S ARE IN INCHES UNLESS	OTHERWISE									
	2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE												
	LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE												
	ON CODE WIRES AND FLEX/24 STRANDED CABLES.												
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.												
		WITH "P".											
	MATERIAL:	HIGH CONDUCTI	UCTIVITY WROUGHT COPPER										
С	FINISH:		ATE UNLESS OTHERWISE	<u> </u>		·							С
	SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.												
					<i>)</i>	Cc Cc	olor coded barrel	markir	ngs				
_	INSTALLATION GUIDE			45° 43°	Wire inspection hole							4	
	DIE CODE = 99 DIE COLOR = Pink												
	DIE GOLOK	- 1 IIIK			<u>†</u>		<u> </u>			4			
							D						
р				Beveled wire entry								В	
В												В	
	c(US ROHS											
	WIF	ISTED BE CONNECTORS WV/207/8 E5/399/3											
	ZAN	VVC2/78.E513913											
	1												
						A	® CELES	TDA	COI	PPO	ΡΔΤΙ	אכ	
						HUYA	76. Hua						
						www.huyaco.cor		yu Dist. Guangzhou 511495.					
Α						WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE							Α
	00 00 00 00	Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.				MATERIAL HIGH-CONDUCTIVITY	PRT. NO.		CALE	ТНІ	RID ANGLE PR	OJECTION	
		Ruby Feng Sinia Qiu DWN CHK				WROUGHT COPPER	DA7158F		N ⁻	-	6 F	\supset	
	REV DATE		DESCRIF			ELECTRO TIN PLATE	186-cp12	81 ~	IN	CH	\$ \frac{1}{2}		
		4		3	4	2				1			
					•								