									1								$\overline{}$
			4				3		<u> </u>	2		<u> </u>		1			
·	DISCL	OSED IN CON	NFIDENCE AND	NOT TO BE		CELESTRA, IS D, USED OR			CELESTR CAT.NO		E SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	H ±0.01	
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.					DA7112F-2		1325/24 = 535	1/2	1.69	1.81	0.28	0.97	
									2707112172	700 101111	kcmil 427/.0342	"-	1.00	1.01	0.20	0.07	
D																	D
D	N	IOTE:		DIMENSION CIFIED.	IS ARE IN IN	NCHES UNLESS	OTHERWISE										
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE								H / BOLT SIZE								
	LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS																
	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																
	N	MATERIAL:	HIGI	H CONDUCT	TIVITY WRO	UGHT COPPER	₹			<u> </u>	В 🖚						
С	F	INISH:				SS OTHERWIS	E			1							С
					TE PER MIL D.WITH "SP"	- 1 -16366. FOR SILVER.											
									,	\searrow	color coded barrel	markiı	ngs	\leftarrow	$\overline{}$		
									Wire inspection hole								
	•	NSTALLATIONE CODE =							\$								\leftarrow
	•	DIE COLOR :							•		+						
											<u>†</u>			-	_		
						,				Beveled v	D vire entry						
В			ر) ر		Pall	, C				Develed v	ine entry						В
					2002/95/E	>											
			LIST WIRE CONF														
			28000/2/16	.E513813													
	1																
											R CELES	STRA	CO	RPO	RATIO	ON	
									HUYA 76. Huancun Rd. Zhongcun To						un Tow	'n.	J
										www.huyaco.co	n Panyu Dist. Guangzhou 511			11495.			
Α										WIRE CONNECTORS AND SOLDERING							Α
										LUGS FOR CODE AND FLEX CABLE							
	00	23-Aug-25	g-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.							MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE DA7112F-241 NTS							
ı	REV	DATE	DWN	СНК		DESCR	PTION		ECN	FINISH ELECTRO TIN PLATE	DWG. NO. 186-cp12	283	nit In	СН	₩ L	\Box	
			4		1		3	Z	\uparrow	2				1			
									I								