													\equiv
		4		3	\bigvee	2				1			
•		ON THIS DRAWING IS THE F IFIDENCE AND NOT TO BE R			CELES		E SIZE	BOLT	В	С	D	Н	
		FOR WHICH FURNISHED.	ET NOBOOLB, OSEB ON		CAT.N	0002	FLEX 1325/24 = 535	SIZE	MIN	±0.04	±0.015	±0.01	
					LA755	8F 750 kcmil	kcmil	5/8	1.58	1.94	0.27	1.06	
D													D
	NOTE:	1. ALL DIMENSIONS SPECIFIED.	S ARE IN INCHES UNLESS	OTHERWISE									
	LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE												
	ON CODE WIRES AND FLEX/24 STRANDED CABLES.												
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.												
		WITH "P".											
	MATERIAL:	HIGH CONDUCT	VITY WROUGHT COPPER										
С	FINISH:		ATE UNLESS OTHERWISE	≣		•							С
			E PER MIL - T -16366. WITH "SP" FOR SILVER.										
						\nearrow	color coded barrel	markin	gs		_		
					°	out.							
_	INSTALLATION GUIDE				45° ±3°	Wire inspection hole							
		DIE CODE = 99 DIE COLOR = Pink											
	DIE COLOR	- 1 IIIK			<u> </u>		 			H			
							D						
_						Beveled wire entry							_
В											В		
	c (US RoHS											
	L WIR	ISTED LE CONNECTORS INVESTIGE E513913											
	ZM	√V/2/7/8,E513913											
	1												
							R CELES	TDA	COE		DATI	אכ	
						HUY	76. Hua						
						www.huyaco.com Panyu Dist. Guangzhou							
Α						WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE							Α
	00 00 7 ==	02-Dec-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.				MATERIAL HIGH-CONDUCTIVIT	PRT. NO.		ALE	ТНІ	RID ANGLE PR	OJECTION	
					FONI	WROUGHT COPPER	LA7558F		NT	S .	6 F	$\neg 1$	
	REV DATE	DWN CHK	DESCRI		ECN	ELECTRO TIN PLATE	186-cp12	95 51	INC	CH	¥ -		. [
		4		3	4	2				1			
					•								