								I									
			4				3		7	2				•	1		
1		THE INFORMATION ON THIS DRAWING IS THE PROERTY OF CELESTRA, IS DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR				CELESTRA		WIRE SIZE		BOLT				Н			
			FOR WHICH		KEFKODOC	LD, OSLD OK			CAT.NO LA1178F		FLEX	SIZE 7/8	MIN 1.83	±0.04		±0.01	
								l	LATITOF	1000 KCMII	1000 Navy	1/6	1.03	2.37	0.30	1.25	
D																	D
	N	IOTE:			IS ARE IN	INCHES UNLES	S OTHERWISE			Н	∕─BOLT SI	ZE					
			SPECIFIED.														
		 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE 							By C								
	ON CODE WIRES AND FLEX/24 STRANDED CABLES.																
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS																
		OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".								B →							
	M	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER															
С	F	INISH:		ELECTOR-TIN PLATE UNLESS OTHERWISE							Color coded barrel markings						С
		SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.															
									45° ±3°	Vie colar	lire inspection ho	le					
									4								
_	۱ ,								↓		<u> </u>						
	INSTALLATION GUIDE DIE CODE = 125								'			4	_				
	D	IE COLOR :	= White								D						
										[∟] Beveled wi	re entry						
В					ı												В
			C (L JU S	Rob	HS,											
			LIST	TED .													
			WIRE CONN ZMVV/2/7/8														
	1																
											® CELES	TP/	CO	RPO	PATIC	N	
									++	HUYA					un Towr		
									+	www.huyaco.com Panyu Dist. Guan							
Α									TITLE WIRE CONNECTORS AND SOLDERING								Α
										LUGS FOR CODE AND FLEX CABLE							
	00	04-May-25	Ruby Feng	Sinia Qiu		Celestra Stand	ards Spec. Initiale	ed.		MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	LA1178F			TS	HRID ANGLE PR	DJECTION	
1	REV	DATE	DWN	CHK		DESCF	RIPTION		ECN F	ELECTRO TIN PLATE	DWG. NO. 186-cp13	09	TINIT 1N	ICH	⊕ Ł		ı
			4				3	4		2				,	1		
					•			I				•					