								I									
			4				3	4	7	2				1			
ı						F CELESTRA, IS			CELESTRA	•	SIZE	BOLT	В	С	D	Н	1 '
			FOR WHICH	D NOT TO BE I FURNISHED.	REPRODUCE	D, USED OR			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.01	1
							_				4/0 Weld 550/24 = 222 kcmil						
									DA4014F-24		133/.0399	1/4	0.78	1.25	0.15	0.64	
D											259/.0286 637/.0183						I_{D}
D	NO	OTE:	1. ALL	DIMENSION	IS ARE IN I	NCHES UNLESS	S OTHERWISE				0317.0103						15
			SPE	CIFIED.													
			2. ALL	DA,DB,LA,L	B,WP,AL,A	S AND J SERIES	OF CAT.NO.S ARE										
						RS INC." AND "C X/24 STRANDEI											
			ON	CODE WINE	3 AND FLL	.X/24 31 KANDEI	J CABLES.			Ц	/-BOLT SI	7F					
						HAS NOT PEEP I THE SUFFIX O					/ 202. 0						
				H "P".	LOIFILD II	THE SUFFIX O	FILL CALINO.				1						
	М	ATERIAL:	HIG	H CONDUCT	CIVITY WRO	OUGHT COPPER	2			Huya Huya	C C						
		NISH:	E1 E	CTOD TINI D		ESS OTHERWIS	_				<u> </u>						
С	FI	INIOH.		CIOR-TIN P			C			'							С
			SU	FIX CAT.NO	.WITH "SP'	' FOR SILVER.				-	3 -						
\rightarrow	IN	ISTALLATIO	ON GUIDE								olor coded barrel	markır	ngs				\leftarrow
		IE CODE = (IE COLOR =	-						/5° /*43°	Colar	Vire inspection ho	le					7
		IL COLOIN -	- Tellow						45		viic inspection ne						
									<u> Y</u>		 			4			
В				. /							D						В
		c((UL) _{US}	.RoHS						Beveled wi	re entry						
		i	ISTER	2002/95/EC						2010104 111	. o ona y						
		WIR ZM	E CONNECTORS VV/2/7/8.E513913														
											(R) CELES	TRA	CO	RPO	RATIO	NC	1
									_	HUYA	76. Hua						
				 					+	www.huyaco.co	_						
Α						_			 	TLE WIRE COI	VINIECTORS		201	DE	SINIC		Α
			WIRE CONNECTORS AND SOLDERII														
									FOR CODE AND FLEX CABLE								
	00	14-Dec-25	Ruby Feng	Sinia Qiu		Celestra Standa	rds Spec. Initialed.			ATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	DA4014F-241			TS THE	RID ANGLE PF	OJECTION	
1	REV	DATE	DWN	CHK		DESCR	PTION		ECN F	NISH ELECTRO TIN PLATE	DWG. NO. 186-cp13	54 U	init In	ICH .	⊕ £] ,
			4				3	4	7	2				1			
					•							•					