		4		3	\psi	2			1		
I	DISCLOSED IN		THE PROERTY OF CELESTRA, BE REPRODUCED, USED OR ED.	IS	CELEST CAT.N	101		BOLT B SIZE MIN	-	H D 0.01 ±0.015	
					LA081	4A 8 AWG	23 Navy #8 Weld 37/24 = 14.9 kcmil #6 SOL	1/4 0.65	0.42 0	.18 0.08	
D	D NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.								.		D
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.							<u>, </u>			
PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".								B × S			_
	MATERIA	L: HIGH COND	UCTIVITY WROUGHT COI	PPER				,			
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry								С		
\rightarrow	INSTALLATION GUIDE DIE CODE = 21 DIE COLOR = Red					Wire inspection hole					
В	LISTED COLUS ROHS										В
_		WIRE CONNECTORS ZMVV/2/7/8.E513813									_
						HUYA www.huyaco.co	76. Huar	TRA CO ncun Rd. Z ist. Guang	hongcun ⁻	Town.	
А						WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE					
	00 04-May	00 04-May-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.				MATERIAL HIGH-CONDUCTIVITY PRT. NO. WROUGHT COPPER LA0814A NTS					
	REV DAT		K DES	SCRIPTION	ECN	FINISH ELECTRO TIN PLATE	DWG. NO. 186-cp139	5 UNIT IN	NCH C] ,
		4	l	3	4	2			1		