	4 3		\downarrow	2		11					
ı	DISCLOSED IN CO	N ON THIS DRAWING IS THE I NFIDENCE AND NOT TO BE F T FOR WHICH FURNISHED.		S	CELEST CAT.N		FLEX	BOLT B SIZE MIN	C ±0.04		D .015
					LA0810AF	2-260 8 AWG	23 Navy #8 Weld 37/24 = 14.9 kcmil #6 SOL	#10 0.52	0.41	0.18 0	.08
D	NOTE:	ALL DIMENSION SPECIFIED.	S ARE IN INCHES UNL	ESS OTHERWISE							D
		LISTED BY "UND	B,WP AND J SERIES OF ERWRITERS INC." AN S AND FLEX/24 STRAN	D "CSA" FOR USE		D					
			.WITH "L" HAS NOT PE ECIFIED IN THE SUFFI		B						
С	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE					90° 7					
J	SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry— H										
-	INSTALLATION GUIDE DIE CODE = 21 DIE COLOR = Red					Wire inspection hole					
В		CUL US LISTED WIRE CONNECTORS	RoHS 2002/95/EC	I	BOLT SIZE Color coded barrel markings						
		WINE CONNECTIONS ZMVV/2/7/8 E513813									_
						HUYA www.huyaco.com	76. Hua	TRA CO ncun Rd. Z Dist. Guang	hongcur	n Town.	1
Α						TITLE WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE MATERIAL HIGH-CONDUCTIVITY PRT. NO. LA0810AP-260 SCALE NTS THRID ANGLE PROJECTION NTS					
	REV DATE	DWN CHK	DES(CRIPTION 3	ECN_	ELECTRO TIN PLATE	DWG. NO. 186-cp140)1 UNIT II	_{VCH} ∜	# <u>_</u>	<u> </u>
		4	I	S	4	۷		I	I		