		4	4		1		3	+	7	2		1		1			
ı	DISCLOSE		ICE AND N	NOT TO BE REF	OERTY OF CELESTR PRODUCED, USED O				CELESTRA CAT.NO	A WIRE CODE	SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	H ±0.01	D ±0.015	
									DA0638A-2	6 AWG	30 Navy 6 Weld 133/.014 61/24 = 24.6 kcmil	3/8	0.84	0.62	0.22	0.06	
D	NOT	≣: 1.	ALL DI SPECI		ARE IN INCHES U	INLESS (	OTHERWISE									D	
		2.	LISTE	D BY "UNDE	WP,AL,AS AND J S RWRITERS INC." / AND FLEX/24 STR	AND "CS											
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																
		ERIAL:			TTY WROUGHT CO							90° X					
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.  Beveled wire entry												С				
-	INSTALLATION GUIDE DIE CODE = 24 DIE COLOR = Blue								Wire inspection hole								
В	BOLT SIZE Color coded barrel markings												В				
		WIRE CONNECTO ZMVV/2/7/8.E513															_
										HUYA www.huyaco.com		ancun	Rd. Zł	nongci	un Tow	'n.	
А																	А
	00 01-	Dec-25 Ruby	/ Feng	Sinia Qiu			ls Spec. Initialed.			MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	DA0638A-250			TS	RID ANGLE P	ROJECTION	
	REV [		WN   1	CHK	DE	ESCRIP	TION 3	$\Lambda$	ECIV	ELECTRO TIN PLATE	DWG. NO. 186-cp14	.17 U	NIT IN	іСН - 1	<b>+</b> E		
		4	+				S	4	7	۷		1		ı			