		4	1	3	+	2		I	,	1		
ı	DISCLOSED IN CON	I ON THIS DRAWING IS THE PRONFIDENCE AND NOT TO BE REPETOR WHICH FURNISHED.	DERTY OF CELESTRA, IS RODUCED, USED OR		CELEST CAT.No	RA WIRE	SIZE FLEX	- 1	B C	H ±0.01	D ±0.015	'
	DISLOSED EXCEP	FOR WHICH FORNISHED.			LA0614AP	-260 6 AWG	30 Navy 6 Weld 133/.014 61/24 = 24.6 kcmil	1/4 0	.64 0.48	0.22	0.08	
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.									D		
		ON CODE WIRES A	VP AND J SERIES OF RWRITERS INC." AND ND FLEX/24 STRAND VITH "L" HAS NOT PEE		D B S [*] *S							
	MATERIAL:	WITH "P".	IFIED IN THE SUFFIX TY WROUGHT COPP									
С	ENTIRE ENTRE THE PLATE UNITED AT FRANCE										С	
→	INSTALLATION GUIDE DIE CODE = 24 DIE COLOR = Blue					Wire inspection hole						
В		C UL US	ROHS	E	BOLT SIZE Color coded barrel markings							
		WIRE CONNECTORS ZMVV/27/8 E513813										
						HUYA www.huyaco.com		ncun Rd	ORPO . Zhongo ngzhou 5	un Towi		
Α						WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE						
	00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed. REV DATE DWN CHK DESCRIPTION				FON	MATERIAL HIGH-CONDUCTIVITY PRT. NO. LA0614AP-260 NTS FCN FINISH TERROR TO THE PROPERTY OF THE					OJECTION	
	REV DATE	DWN CHK 4	DESC	3	ECN	electro tin plate	186-cp14	46	INCH ,	1	7	