		4	1	3	$\downarrow$		2			1			
ı	DISCLOSED IN CO	NON THIS DRAWING IS THE NFIDENCE AND NOT TO BE F T FOR WHICH FURNISHED.		S		STRA	WIRE CODE	SIZE FLEX	BOLT B SIZE MIN	C ±0.04	H ±0.01	D ±0.015	
					DA0	438A	4 AWG	40-50 Navy 133/.0177 49/.029 91/24 = 36.7 kcmil	3/8 0.66	0.61	0.27	0.07	
D	NOTE:	ALL DIMENSION     SPECIFIED.								D			
		LISTED BY "UND	B,WP AND J SERIES O DERWRITERS INC." AN S AND FLEX/24 STRAN										
			).WITH "L" HAS NOT PI ECIFIED IN THE SUFFI		B								
С	MATERIAL: FINISH:	HIGH CONDUCT ELECTOR-TIN P SPECIFED PLAT		90°									
	SUFFIX CAT.NO.WITH "SP" FOR SILVER.  Beveled wire entry												
$\rightarrow$	INSTALLATION GUIDE DIE CODE = 29					Wire inspection hole							
	DIE COLOR = Gray							Die Color					
В		c <b>(UL</b> )us		BOLT SIZE — Color coded barrel markings —									
		LISTED WIRE CONNECTORS ZMVV/2/7/8.E513813											
							UYA w.huyaco.con	76. Hua	TRA CC ncun Rd. Z ist. Guanç	hongcı	ın Tow		
Α													А
	00 23-Aug-25	00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.				MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRI						OJECTION	
	REV DATE	DWN CHK	DES	CRIPTION	ECN	FINISH	ELECTRO TIN PLATE	DWG. NO. 186-cp14	6 UNIT	NCH	<b>(</b> E		
		4		3	4		2			1			