					_										
			4			3	abla	7	2				1		_
•	THE IN	NFORMATION OSED IN CON	ON THIS DRA	AWING IS THE D NOT TO BE F	PROERTY OF CELESTR REPRODUCED, USED O	A, IS		CELESTRA			-	ВС	H	D	['
			T FOR WHICH					CAT.NO	CODE	FLEX 40-50 Navy	SIZE N	IIN ±0.0	4 ±0.01	±0.015	4
								DA0410A-25	50 4 AWG	133/.0177 49/.029 91/24 = 36.7 kcmil	#10 0.	.53 0.55	0.28	0.09	
D									·		•		•		$_{D}$
D	N	OTE:		DIMENSION CIFIED.	S ARE IN INCHES U	INLESS OTHERWISE									
		 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE 								1	1	D			
					S AND FLEX/24 STR										l
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.								$\frac{ }{B} \triangleright \int$	1					
		WITH "P".													
	M	IATERIAL:	HIGI	H CONDUCT	IVITY WROUGHT C	OPPER					30,				
С	FI	INISH:			LATE UNLESS OTH E PER MIL - T -1636										С
	SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry————————————————————————————————————														
									,						
_								/—Wire inspection hole							
\rightarrow	INSTALLATION GUIDE DIE CODE = 29						The moposition follows:							\leftarrow	
	DI	IE COLOR :	= Gray						8-3-	\perp $\stackrel{\frown}{C}$					
									I			Die	Color		
_					. /										
В	B BOLT SIZE Color coded barrel markings										В				
			LICT	TEN	2002/95/EC										
			WIRE CONF												
	1														
									LIIVA	® CELES	TRA C	ORPC	RATI	ON	
									HUYA		ncun Rd				
Α									www.huyaco.cor		oist. Gua				A
^	TITLE						WIRE CONNECTORS AND SOLDERING					^			
								LUGS FOR CODE AND FLEX CABLE							
	\vdash	23-Aug-25	Ruby Feng	-		Standards Spec. Initia	led.		MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	DA0410A-250	SCALE	NTS	HRID ANGLE F	ROJECTION	
1	REV	DATE	DWN	CHK	D.	ESCRIPTION		ECN F	ELECTRO TIN PLATE	DWG. NO. 186-cp14	58 UNIT	INCH] ,
	4 3						4		2				1		
							I								