| | - | | | | | | 1 | | | | | | | | | |
|---------------|--|-------------------------|-------------|-------------|-----------------|---------------------|------------------------|------------------------|--|-------------------------|----------|--------|--------|------|--------|--------------|
| | 4 | | 3 | | \checkmark | 7 | 2 | | 1 | | | | | | | |
| I | THE INFORMATION ON THIS DRAWING IS THE PROERTY OF CELESTRA, DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR | | | | | CELESTR | | E SIZE | BOLT | В | C | H | D | | | |
| | DISLOSED EXCEP | | | | , | | | CAT.NO | | FLEX 60 Navy #4 Weld | SIZE | MIN | ±0.04 | | ±0.015 | |
| | | | | | | | | DA0256A | A 2 AWG | 125/24 = 50.5 kcmil | 5/16 | 0.88 | 0.59 | 0.30 | 0.11 | |
| | | | | | | | | | | | | | | | | |
| D | NOTE | 4 411 | | | | | | | | | | | | | | D |
| | NOTE: | | CIFIED. | 5 ARE IN IN | CHES UNLES | S OTHERWISE | | | | | | _ | | | | |
| | | | | | SERIES OF C | | | | | I | | D | - | | | |
| | LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. | | | | | | | | | | | | | | | |
| | PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | WITH "P". | | | | | | | 0°×× | | | | | | | | |
| | MATERIAL: | HIGI | H CONDUCT | IVITY WROL | JGHT COPPE | R | | | | | <u> </u> | | | | | |
| С | FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. | | | | | | Beveled wire entry — H | | | | | | | | С | |
| | SUFFIX CAT.NO.WITH "SP" FOR SILVER. | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | / Wire inspection hole | | | | | | | | |
| \rightarrow | INSTALLATIO | INSTALLATION GUIDE | | | | | | | | | | | | | | \leftarrow |
| | DIE COLOR | | | | | | | | |)— c | | | | | | |
| | | | | | | | | | | | | | Die C | olor | | |
| | | | | | | | | | | | | | | | | |
| В | | |) | V | • | | | BC | OLT SIZE —— | Color coded bar | el mar | rkings |] | | | В |
| | | C | J US | RoHS | 5 | | | | | | | | | | | |
| | | LIST | TED | | | | | | | | | | | | | |
| | | WIRE CONF ZMVV/2/7/8 | | | | | | | | | | | | | | |
| | - | | | | | | | | | | | | | | | — |
| | | 1 | | | | | | | | | | | | | | |
| | | | | | | | | | HUY | R CELES | | | | | | |
| | | | | | | | | | www.huyaco.cc | | | | | | n. | |
| А | | | | | | | | | - | | | | | | | А |
| 7. | | | | | | | | | ITTLE WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | 00 23-Aug-25 | Ruby Feng | Sinia Qiu | C | Celestra Standa | ards Spec. Initiale | ed. | | MATERIAL HIGH-CONDUCTIVIT WROUGHT COPPER | DA0256A | | | TS THE | | | |
| 1 | REV DATE | DWN | СНК | | DESCR | IPTION | | ECN | ELECTRO TIN PLATE | DWG. NO. 186-cp14 | 96 | nit IN | ICH . | ŒE | | 1 |
| | | 4 | | | | 3 | 4 | 7 | 2 | | | | 1 | | | |
| | | | | | | | I | | | | | | | | | |