			4				3	\neg	7	2				1				
I	THE IN	IFORMATION	NON THIS DRA	WING IS THE	PROERTY OF CELESTR REPRODUCED, USED C	RA, IS DR			CELESTRA	WIRE		BOLT	В	C	Н	D		
			T FOR WHICH						CAT.NO	CODE	FLEX 60 Navy #4 Weld	SIZE	MIN	±0.04		±0.015		
									DA0256A-260	2 AWG	125/24 = 50.5 kcmil	5/16	0.70	0.61	0.30	0.11		
										·								
D																	D	
	N	OTE:		DIMENSION CIFIED.	NS ARE IN INCHES U	JNLESS C	DTHERWISE						П					
					B,WP AND J SERIES													
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																
												>	ĴŤ					
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.																	
		WITH "P".								°×××								
		ATERIAL:			TIVITY WROUGHT C							96						
С	FI	NISH:			PLATE UNLESS OTH TE PER MIL - T -1636												С	
	SUFFIX CAT.NO.WITH "SP" FOR SILVER.							Beveled wire entry —/ H										
										— Wire in	spection hole							
\rightarrow	IN	ISTALLATIO	ON GUIDE											\leftarrow			4	
		IE CODE = IE COLOR =															7	
			- BIOWII															
											Y			Die C	olor			
									BOI		Color coded barr	el mar	kings					
В			_ (U) 10					DOI				0				В	
					2002/95/EC													
			ZMVV/2/7/8															
												TRA		RPO	RATI	ON		
										ΗΨΥΑ						n.		
									<u> </u>	www.huyaco.cor	n Panyu [Dist. G	uangz	zhou 5	11495.			
A			<u> </u>			TITLE WIRE CONNECTORS AND SOLDE						_DEF	RING	NG A				
											R CODE ANI							
	00	01-Jul-25	Ruby Feng	Sinia Qiu	Celestra	Standards	s Spec. Initialed.		MA	TERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	PRT. NO. DA0256A-260		CALE		RID ANGLE PI	ROJECTION		
	REV	DATE	DWN	СНК	DI	ESCRIP	TION		ECN FIN		DWG. NO. 186-cp15	04 U	NIT	ICH -	@ E			
			4	1	<u> </u>		3	Δ	I	2				1				
			•		I		-	4		—		I						