	-	4		3	<b>+</b>		2				1			
ı	DISCLOSED IN CON	ON THIS DRAWING IS THE IFIDENCE AND NOT TO BE FOR WHICH FURNISHED.	PROERTY OF CELESTRA, I REPRODUCED, USED OR	S	CELES CAT.I		WIRE	SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	H ±0.01	D ±0.015	I
	DISLOSED EXCEPT	FOR WHICH FURINISHED.			LA021	0A	2 AWG	60 Navy #4 Weld 125/24 = 50.5 kcmil	#10	0.65	0.59	0.30	0.11	
D	NOTE:	1 ALL DIMENSION	IS ARE IN INCHES UNL	ESS OTHERWISE		·								D
	NOTE:	SPECIFIED.				<u>D</u>								
		LISTED BY "UNI	B,WP AND J SERIES O DERWRITERS INC." AN S AND FLEX/24 STRAN	D "CSA" FOR USE										
			D.WITH "L" HAS NOT PI PECIFIED IN THE SUFFI		B S S S S S S S S S S S S S S S S S S S									
	MATERIAL:	HIGH CONDUCT	TIVITY WROUGHT COP	PER		99								
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.  Beveled wire entry										С			
	INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown					Wire inspection hole								
В		CUL)US LISTED WIRE CONNECTORS	RoHS 2002/95/EC			BOLT SIZ	E—	Color coded barr	el mari	kings -				В
		ZMVV/27/8.E513813												
							UYA huyaco.con		ncun F	Rd. Zh	ongcu	ın Towi		
А			WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								Α			
		Ruby Feng Sinia Qiu		ndards Spec. Initialed.		W	GH-CONDUCTIVITY ROUGHT COPPER	LA0210A	-	CALE NT	-s	ID ANGLE PR	OJECTION	
	REV DATE	DWN CHK	DES	CRIPTION 3	ECN	FINISH ELE	ECTRO TIN PLATE	DWG. NO. 186-cp152	21 UN	IN	сн   <sup>1</sup>	ΨΞ		
	_		I	•	+		_		I		•			