THE INFORMATION OF THE PROPERTY OF CELESTRA, IS DISCLOSED BY COMPOSING WHICH FURNISHED NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DADBLALB WP ALLAS AND J SERIES OF CATINO S ARE LISTED BY 'UNDERWITHERS INC.' AND 'CSA' FOR USE ON COOPE BY 'UNDERWITHERS INC.' AND 'CSA' FOR USE ON COOPE BY 'UNDERWITHERS INC.' AND 'CSA' FOR USE ON COOPE WIRES AND FLEX/24 STRANDED CABLES. OTHERWISE SPECIFIED IN THE SUFFIX OF THE CATINO. WITH 'P'. MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFIED FAIR PER MILTI-16368. SUFFIX CATINO.WITH 'SP' FOR SILVER. BEVEICH OF THE SUFFIX OF THE CATINO. WITH 'P'. Wire inspection hole INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown BOLT SIZE Color coded barrel markings Color coded barrel markings	01 ±0.015	1		ı					1				
DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR DISCOSED EXCEPT FOR WHICH FURNISHED. I. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DAJBLALB, WP, ALAS AND J SERIES OF CAT.NO. SARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEXZ4 STRANDED CABLES. PRE-FIX CAT.NO. WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUPFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MILT. 16386. SUFFIX CAT.NO.WITH "SP" FOR SILVER. BEVEILED WITH DISCOVERY OF THE WISE SPECIFED PLATE PER MILT. 16386 SUFFIX CAT.NO.WITH "SP" FOR SILVER. WITH DISCOVERY OF THE WISE BEVEILED WITH DISCOVERY OF THE WISE SPECIFED PLATE PER MILT. 16386. SUFFIX CAT.NO.WITH "SP" FOR SILVER. BEVEILED WITH DISCOVERY OF THE WISE SPECIFED PLATE PER MILT. 16386. SUFFIX CAT.NO.WITH "SP" FOR SILVER. BEVEILED WITH DISCOVERY OF THE WISE SPECIFED PLATE PER MILT. 16386. SUFFIX CAT.NO.WITH "SP" FOR SILVER. COIOT coded barrel markings	01 ±0.015					2	\bigvee	3			4		
DISLOSED EXCEPT FOR WHICH FURNISHED. CATALO LA0210A 2 AWG 60 Navy #4 Weld 125/24 = 50.5 kcmil #10 0.65 0.59 LA0210A 2 AWG 60 Navy #4 Weld 125/24 = 50.5 kcmil #10 0.65 0.59 NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA,DB,LA,LB,WP,ALAS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC," AND "CSA" FOR USE ON CODE WRES AND FLEXY STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFIED PLATE PER MIL - 7 -16366. SUFFIX CAT.NO.WITH "S" FOR SILVER. Bevelled wire entry Wire inspection hole DIE COLOR = Brown BOLT SIZE Color coded barrel markings													
D NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA, DB LALLB, WP ALAS AND J SERIES OF CAT, NO. S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT, NO, WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT, NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL. T. 16366. SUFFIX CAT, NO, WITH "SP" FOR SILVER. Beveled wire entry Wire inspection hole INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown BOLT SIZE Color coded barrel markings	30 0.11	±0.04 ±0.01	MIN			CODE	CAT.NC		RODUCED, USED OR				
D NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA.DB.LA.LB.WP.AL.AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEEVA STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL. T. 16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Bevelled wire entry Wire inspection hole DIE COLOR = Brown BOLT SIZE Color coded barrel markings		0.59 0.30	0.65			2 AWG	LA0210	_					
NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DAD BLALB WP.AL.AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEXZ4'S STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL. T-1-636.6 SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry Wire inspection hole INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown BOLT SIZE Color coded barrel markings					1.20/2 : 00:0 ::0::::								
NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DAD BLALB WP.AL.AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEXZ4'S STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL. T-1-636.6 SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry Wire inspection hole INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown BOLT SIZE Color coded barrel markings	D												
SPECIFIED. 2. ALL DAUBLALB.WP.AL.AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL. T - 16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry Wire inspection hole INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown BOLT SIZE Color coded barrel markings	١٢							S OTHERWISE	RE IN INCHES UNLES	DIMENSIONS	1. ALL	NOTE:	الا
LISTED BY 'UNDERWRITERS INC.' AND 'CSA' FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T - 16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry Wire inspection hole INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown BOLT SIZE Color coded barrel markings			D										
ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T - 16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry Wire inspection hole INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown BOLT SIZE Color coded barrel markings								OF CAT.NO.S ARE	P,AL,AS AND J SERIE	DA,DB,LA,LB	2. ALL		
PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T - 16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry Wire inspection hole INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown BOLT SIZE Color coded barrel markings													
OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T - 16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry Wire inspection hole DIE CODE = 33 DIE COLOR = Brown BOLT SIZE Color coded barrel markings	l —		7 1					J CABLES.	ND I LEX/24 STRAINDL	JODE WINES	ON		
MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL. T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry Wire inspection hole Wire inspection hole DIE CODE = 33 DIE COLOR = Brown BOLT SIZE Color coded barrel markings				В ,									
C FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T - 16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry Wire inspection hole UNSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown BOLT SIZE Color coded barrel markings			,	° ×'n				FINE CALINO.	FIED IN THE SUFFIX (
C FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T - 16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry Wire inspection hole UNSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown BOLT SIZE Color coded barrel markings				90				₹	TY WROUGHT COPPE	H CONDUCTI	HIGH	MATERIAI ·	
SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry Wire inspection hole UNSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown BOLT SIZE Color coded barrel markings													
Beveled wire entry Wire inspection hole INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown BOLT SIZE Color coded barrel markings	C							.⊏				LINI9H;	C
INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown BOLT SIZE Color coded barrel markings COLOR = Brown					⁄ П	eled wire entry —	В		TH "SP" FOR SILVER.	FIX CAT.NO.	SUF		
INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown BOLT SIZE Color coded barrel markings COLOR = Brown													
INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown BOLT SIZE Color coded barrel markings COLOR = Brown		Wire inspection hole											
B DIE CODE = 33 DIE COLOR = Brown BOLT SIZE Color coded barrel markings BOLT SIZE Color coded barrel markings											ON GUIDE	INSTALLATIO	
BOLT SIZE Color coded barrel markings													
CULUS ROHS LISTED WISE CONNECTORS ROHS											= Brown	DIE COLOR	
CULUS ROHS LISTED WIRE COMMETCRIS		Die Color			V_								
CULUS ROHS LISTED WIRE COMMETCRIS						/	_						
		1 .	1::	h	Calar and ad har		В			,			вl
	В		kings -	barrel ma	Color coded bar	T SIZE—							
	В	J '	kings -	barrel ma	Color coded bar	T SIZE —				Police	UI)iie	_	٦
	В] '	kings -	barrel ma	Color coded bar	T SIZE—				RoHS 2002/95/EC	UL) us	С	
	В	J ,	kings -	barrel ma	Color coded bar	T SIZE —				RoHS 2002/95/EC			
	В] '	kings -	barrel ma	Color coded bar	T SIZE —				RoHS, 2002/95/EC			
	В	J ·	kings -	barrel ma	Color coded bar	T SIZE —				RoHS, 2002/95/EC			
HIIV A® CELESTRA CORPOR	_					. 0.22				RoHS			
	TION		COF	_ESTR <i>A</i>		. 0.22				RoHS 2002/96/EC			
	TION own.	ngcun Tow	COF	ESTRA Huancun	R CELES	HUYA				RoHS			
A TITLE WIRE CONNECTORS AND SOLDER	— TION own. 95.	ngcun Tow ou 511495	COF Rd. Zh uangzl	LESTRA Huancun Iyu Dist. G	R CELES 76. Hu Panyu	HUYA				RoHS			
LUGS FOR CODE AND FLEX CABLE	— TION own. 95.	ngcun Tow ou 511495	COF Rd. Zh uangzl	LESTRA Huancun Iyu Dist. G	R CELES 76. Hu Panyu	HUYA				RoHS 2002/HARE			A
00 01-Dec-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed. MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE NTS	— TION own. 95.	ngcun Tow ou 511495 DERING	COF Rd. Zh uangzl	ESTRA Huancun Iyu Dist. G	R CELES 76. Hu Panyu NNECTORS	HUYA vww.huyaco.cor				RoHS			
DEVI DATE DIVIN OUT DECORPTION FOR ENIGH DWG NO LINIT	— TION own. 95.	ou 511495 DERING ABLE	COF Rd. Zh uangzl SOL EX C	ESTRA Huancun Iyu Dist. G RS AND AND FL	R CELES 76. Hu. Panyu NNECTORS R CODE AN	HUYA vww.huyaco.cor WIRE CON LUGS FOR		rds Spec Initialed	Celestra Stand	RoHS 2002/84EC	VV/2/7/8.E513813	23	A
4	TION TOWN. 195.	DERING ABLE	COFRd. Zhuangzl	LESTRA Huancun Iyu Dist. G RS AND AND FL	R CELES 76. Hu Panyu NNECTORS R CODE AN PRT. NO. LA0210A	WIRE CON LUGS FOR WROUGHT COPPER					Ruby Feng	01-Dec-25	A
4 3	TION TOWN. 195.	DERING ABLE THRID ANGLE F	COFRd. Zhuangzl	LESTRA Huancun Iyu Dist. G RS AND AND FL	R CELES 76. Hu. Panyu NNECTORS R CODE AN PRT. NO. LA0210A	WIRE CON LUGS FOR WROUGHT COPPER	ECN	IPTION		Sinia Qiu	Ruby Feng	01-Dec-25	A