			4				3	\triangle	7	2				1			
'				AWING IS THE D NOT TO BE I					CELESTR	•	SIZE	BOLT	В	С	Н	D] '
				FURNISHED.	REPRODUCED	, USED OR			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.01	±0.015	4
5							-		DA0156A-2	50 1 AWG	75 Navy #2 Weld 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.223		0.76	0.70	0.36	0.11	
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.													D			
	2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".										-						
	М	ATERIAL:	HIG	H CONDUCT	TIVITY WROU	JGHT COPPER	₹					%x5	/				
С	FI	NISH:		CTOR-TIN P		SS OTHERWIS T -16366.	E					90					С
			SU	FIX CAT.NO	.WITH "SP" I	FOR SILVER.			Do	volod wire entry	H						
									Бе	veled wire entry —							
\rightarrow	INSTALLATION GUIDE																4
	DIE CODE = 37 DIE COLOR = Green) — C			Die C	olor		7	
В	BOLT SIZE — Color coded barrel markings — BOLT SIZE — Color coded barrel markings — Color coded													В			
																	l
	ļ.,		I														
	$\vdash \vdash$									HUYA	R CELES						
										www.huyaco.co	_						
Α	\vdash		TITLE WIRE CONNECTORS AND SOL						_DEF	ERING							
	$\mid \mid \mid$	LUGS FOR CODE AND FI															
	00	01-Dec-25	Ruby Feng	Sinia Qiu	(Celestra Standa	rds Spec. Initialed.		N	MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	DA0156A-250	S	CALE N	TS	RID ANGLE P	ROJECTION	1
1	REV	DATE	DWN	CHK		DESCR			ECN F	ELECTRO TIN PLATE	DWG. NO. 186-cp15	43 U	nit IN	iCH -	⊕ £] ,
			4				3	4		2				1			
								- 1									