			4				3	abla	7	2				,	1		_
'	THE IN	VFORMATION OSED IN CO	ON THIS DRANGE AN	AWING IS THE D NOT TO BE I	PROERTY OF CELESTRA, IS REPRODUCED, USED OR				CELESTR CAT.NO			BOLT SIZE	B MIN	C ±0.04	H 1 ±0.0′	D ±0.015	
			T FOR WHICH						DA0114A-2		FLEX 225/24 #1 Weld	1/4	0.70	0.76			1
												.,		1	1 5.55	1 ****	1
D			4 411	DIMENIOLON			071150141105										D
	N	IOTE:		. DIMENSION ECIFIED.	IS ARE IN INCH	IES UNLESS	OTHERWISE						Д)			
			2. ALL	DA,DB,LA,L	B,WP AND J SE	ERIES OF CA	T.NO.S ARE						1				
			LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.														
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.															
		WITH "P".															
	М	IATERIAL:	HIG	H CONDUCT	TIVITY WROUG	HT COPPER											
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE						≣		Beveled wire entry H								С
J		SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.						Beveled wire entry ——/									
										∕—Wire i	nspection hole						
_	I IN	INSTALLATION GUIDE															_
	DIE CODE = 37						$-\left(\left(-\right) - \left(-\right) - \left$										
	ט	IE COLOR :	= Green											Die	Color		
														/=			
									В	OLT SIZE—	Color coded barr	el ma	rkings				
В			_(U),,,	Polic												В
					2002/95/EC												
			LIS'	TED INECTORS													
			ZMVV/2/7/	B.E513913													
		I	I											DE 6			-
										HUYA	® CELES						
										www.huyaco.co							
Α																	A
										7	``						
		LUGS FOR CODE AND FLEX CABLE															
	00	23-Aug-25	Ruby Feng	Sinia Qiu	Cele	estra Standar	ds Spec. Initialed	i.		MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	DA0114A-251			ITS TH	\rightarrow	PROJECTION	
	REV	DATE	DWN	CHK		DESCRI	PTION		ECN	ELECTRO TIN PLATE	DWG. NO. 186-cp15	51 U	11 TIN	VCH	O] ,
	4 3							4	7	2					1		
					•			l	l			•					