| | | | 4 | | | 3 | \downarrow | 7 | | 2 | | | | 1 | | | | |
|---------------|--|---|------------------------|----------------------|--|--|--------------|-------------------|-------------------------------|-------------------------------------|--------------|------------|---------------------------|------------|------------|--------------|---|--|
| 1 | DISCL | OSED IN CON | | D NOT TO BE F | PROERTY OF CELESTI REPRODUCED, USED (| | | CELESTF CAT.NC | | WIRE CODE | FLEX | BO SIZ | | C ±0.04 | H ±0.01 | D ±0.015 | , | |
| | | | | | | | | DA0138A- | -251 | 1 AWG | 225/24 #1 V | Veld 3/ | /8 0.83 | 0.76 | 0.39 | 0.12 | 1 | |
| D | | | | | | | | | | | | | | | | | D | |
| | N | OTE: | | DIMENSION CIFIED. | IS ARE IN INCHES U | JNLESS OTHERWISE | | | | | I | 1 | |) | | | | |
| | | | LIST | ED BY "UND | DERWRITERS INC." | S OF CAT.NO.S ARE AND "CSA" FOR USE | | | | | | | | | | | | |
| | ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS | | | | | | | | | | | | | | | | | |
| | OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". | | | | | | | | | | | 90 | × | | | | | |
| | | IATERIAL: | | | | | | | | | | | | | | | С | |
| С | | FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. | | | | | | | Beveled wire entry — H | | | | | | | | | |
| | /Wire inspection hole | | | | | | | | | | | | | | | | | |
| \rightarrow | | NSTALLATIO | | | | | | | | | | | | | | \leftarrow | | |
| Ľ | DIE CODE = 37 DIE COLOR = Green | | | | | | | | | | | | | | | | 7 | |
| | | | | | | | | В | BOLT S | IZE | Color codeo | l barrel r | narkings | | | | | |
| В | | | C) | Dus | RoHS | | | | | | | | | | | | В | |
| | | | LIST | red | 2002/95/EC | | | | | | | | | | | | | |
| | | | WIRE CON ZMVV/2/7/8 | | | | | | | | | | | | | | | |
| | | 1 | 1 | | | | | | | | | _ | | | | | | |
| | | | | | | | | | | UYA | 76 | . Huancı | RA CO un Rd. Zl | hongcı | in Tow | | | |
| А | | | | | | | | | | w.huyaco.com | | | . Guang: | | | | A | |
| | | | | | | | | | WIRE CONNECTORS AND SOLDERING | | | | | | | | | |
| | | | Ruby Feng | Sinia Qiu | Celestra | Standards Spec. Initia | led. | | | HIGH-CONDUCTIVITY WROUGHT COPPER | DA0138 | A-251 | | TS THR | | | | |
| 1 | REV | DATE | DWN | СНК | D | ESCRIPTION | ٨ | ECN | FINISH | ELECTRO TIN PLATE | DWG. NO. 186 | 6-cp1553 | unit IN | ICH | ŧ - | |] | |
| | | | 4 | | | 3 | 4 | 7 | | 2 | | | | 1 | | | | |