	4				3	\square	7	2				1			_	
					PROERTY OF CELESTRA EPRODUCED, USED OR			CELESTRA	WIRE		BOLT	В	С	Н	D	
			FOR WHICH I					CAT.NO	CODE	FLEX 75 Navy #2 Weld	SIZE	MIN	±0.04	±0.01	±0.015	4
P								LA0110A-250	1 AWG	150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.223	#10	0.56	0.70	0.36	0.11	
D	D NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.														D	
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.															
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".															
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER									/						
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С				
		Beveled wire entry — H														
\rightarrow		ISTALLATIO					/Wire inspection hole						\leftarrow			
В		IE CODE = = IE COLOR =		Dus	RoHS	BOL	BOLT SIZE Color coded barrel markings							В		
					ZWZIASICO											
																-
									HUYA 76. Hua			TRA CORPORATION ncun Rd. Zhongcun Town. Dist. Guangzhou 511495.				
A									TITLE WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE							A
	00	23-Aug-25	Ruby Feng	Sinia Qiu	Celestra S	tandards Spec. Initialed		MAT	ERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	PRT. NO. LA0110A-250	S	CALE N		ID ANGLE PF	ROJECTION	1
I	REV	DATE	DWN	СНК	DE	SCRIPTION		ECN FINIS		DWG. NO. 186-cp15	66 ^U	NIT IN	СН	⊕ E		
			4			3	4		2				1			
							I									