		4		3	\downarrow	2			1		
ı	DISCLOSED IN CO	I ON THIS DRAWING IS THE F NFIDENCE AND NOT TO BE R T FOR WHICH FURNISHED.		S	CELES CAT.N		SIZE FLEX	BOLT B SIZE MIN	C ±0.04 ±	H D 0.01 ±0.015	
					DA103	8A 1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0254	3/8 0.93	0.75	0.13	
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.										D
		LISTED BY "UND	S,WP AND J SERIES O ERWRITERS INC." AN S AND FLEX/24 STRAN		D						
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".					B					
	MATERIAL:										
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry									С	
→	INSTALLATION GUIDE DIE CODE = 42 DIE COLOR = Pink					Wire inspection hole					
В	CUL US ROHS					BOLT SIZE Color coded barrel markings					
		WIRE CONNECTORS ZMVV/2/7/B.E513B13									_
						HUYA www.huyaco.co	76. Hua	TRA CO ncun Rd. Z ist. Guang	hongcun	Town.	
Α						WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE					
	_	Ruby Feng Sinia Qiu		ndards Spec. Initialed.		MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	DA1038A		ITS THRID A	NGLE PROJECTION	1
	REV DATE	DWN CHK	DES	CRIPTION 3	ECN	FINISH ELECTRO TIN PLATE	DWG. NO. 186-cp158	2 UNIT II	vcн Ч 1]
		-T	I	Ü	4	~		l	•		