		4		3	\downarrow	2			1		
ı	DISCLOSED IN CC	N ON THIS DRAWING IS THE NFIDENCE AND NOT TO BE I T FOR WHICH FURNISHED.		S	CELES CAT.N		FLEX	BOLT B SIZE MIN	C ±0.04 ±	H D 0.01 ±0.015	<u></u>
					DA101	2A 1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0254	1/2 1.25	0.75	0.40 0.13	
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.										D
		LISTED BY "UNI	B,WP AND J SERIES O DERWRITERS INC." AN S AND FLEX/24 STRAN	D "CSA" FOR USE		D					
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".					B					
	MATERIAL:		CONDUCTIVITY WROUGHT COPPER								
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry										С
-	INSTALLATION GUIDE DIE CODE = 42 DIE COLOR = Pink					Wire inspection hole					
В	CUL US LISTED WIRE CONNECTORS					BOLT SIZE Color coded barrel markings					
		ZMVV/2/7/8 E513813									_
						HUYA www.huyaco.co	76. Huar	TRA CO ncun Rd. Z ist. Guang	hongcun	Town.	
Α						WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE					
	00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.				MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER DA1012A SCALE NTS FINISH DWG. NO. 196 co1593 UNIT NACL.					ī	
	REV DATE	DWN CHK	DES	CRIPTION	ECN	FINISH ELECTRO TIN PLATE	DWG. NO. 186-cp158	3 UNIT IN	ICH 4	# 	
		4	I	3	4	2		I	1		