| | 4 | | 3 | | 4 | 7 | 2 | | 1 | | | | | | |
|------------|--|--------------|----------------------|--|--------------------------|--|---|--|--|--------------|----------|------------|------------|-------------|--------------------|
| I | | NFIDENCE AND | NOT TO BE I | PROERTY OF CELESTRA REPRODUCED, USED OR | IS | | CELESTRA CAT.NO | WIRE CODE | SIZE FLEX | BOLT SIZE | B MIN | C ±0.04 | H ±0.01 | D ±0.015 | |
| | | | | | | | DA1014A-250 | 0 1/0 AWG | 100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0254 | 1/4 | 0.70 | 0.76 | 0.39 | 0.12 | |
| D | NOTE: | | DIMENSION CIFIED. | IS ARE IN INCHES UN | LESS OTHERWISE | | | | | | | | | D | |
| | | LIST | ED BY "UND | B,WP AND J SERIES (DERWRITERS INC." AI S AND FLEX/24 STRA | ND "CSA" FOR USE | | | | | | | | | | |
| | | OTH | | D.WITH "L" HAS NOT F ECIFIED IN THE SUFI | | | | | | | | | | | |
| | | | | TIVITY WROUGHT CO | | | | | | 30 1 | | | | | _ |
| С | FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry | | | | | | | | | | | | С | | |
| \uparrow | INSTALLATION GUIDE DIE CODE = 42 DIE COLOR = Pink | | | | | | Wire inspection hole | | | | | | | | \bigtriangledown |
| В | B BOLT SIZE Color coded barrel markings | | | | | | | | | | | | В | | |
| | | | | | | | | | | | | | | | — |
| | | | | | | | HUYA® CELESTRA CORPORATIO Www.huyaco.com 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495. | | | | | | | | |
| A | | | | | | TITLE WIRE CONNECTORS AND SOLDERING ' LUGS FOR CODE AND FLEX CABLE | | | | | | | | А | |
| | | Ruby Feng | | | andards Spec. Initialed. | - | | TERIAL HIGH-CONDUCTIVITY WROUGHT COPPER | PRT. NO. DA1014A-250 DWG. NO. 100 ar 45 | _ | NIT | TS _ | | | |
| | REV DATE | DWN 4 | СНК | DES | SCRIPTION 3 | 4 | | ELECTRO TIN PLATE | ^{Dwg. NO.} 186-cp15 | 84 | ' IN | сн 1 | ¥ - | | |