			4				3		7	2				1					
'	THE IN	NFORMATION	ON THIS DRA	WING IS THE	PROERTY OF CELESTREPRODUCED, USED	TRA, IS			CELESTRA			BOLT	В	С	Н	D	'		
			FOR WHICH		NEI NOBOCEB, OSEB	OIX			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.01	±0.015			
									DA1012A-28	50 1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0254	1/2	1.07	0.80	0.39	0.12			
D																	D		
D	N	OTE:		DIMENSION CIFIED.	IS ARE IN INCHES	UNLESS	OTHERWISE												
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE																		
	ON CODE WIRES AND FLEX/24 STRANDED CABLES.																_		
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".								B										
	M	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																	
С	F	INISH:			LATE UNLESS OT		<u> </u>					- ,					С		
J					TE PER MIL - T -163 D.WITH "SP" FOR S				_		H								
									Beveled wire entry — H										
\rightarrow	INSTALLATION GUIDE DIE CODE = 42							Wire inspection hole								\leftarrow			
		IE COLOR :																	
)—— С								
					,									Die ¢	olor				
В			_(U) II C	Police				ВС	OLT SIZE—	Color coded barr	el mar	kings				В		
					2002/95/EC														
			LIST WIRE CONN ZMVV/2/7/8	EU ECTORS E513913															
	1																		
										1 1 1 1 3 / A	(R) CELES	TRA	CO	RPOI	RATIO	ON			
										HUYA	76. Hua	ncun	Rd. Zh	nongci	ın Tow	'n.			
٨									www.huyaco.com Panyu Dist. Guangzhou 511495.							_			
Α										S AND SOLDERING					Α				
									LUGS FOR CODE AND FLEX CABLE										
	00	23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					N	ATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	DA1012A-250	S	CALE N	TS	RID ANGLE P	ROJECTION	ION				
1	REV	DATE	DWN	CHK		DESCRIF	PTION		ECN F	NISH ELECTRO TIN PLATE	DWG. NO. 186-cp15	87 U	nit In	ICH -	⊕ €	\exists			
			4				3	4	\	2				1					
								ı											