			4				3		7	2				1					
'	THE IN	FORMATION	ON THIS DRA	WING IS THE	PROERTY OF CELESTE REPRODUCED, USED C	RA, IS			CELESTRA			BOLT	В	С	Н	D	'		
			FOR WHICH		KEI KODOCED, OSED C				CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.01	±0.015			
									DA1014A-26	60 1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0254	1/4	0.64	0.75	0.39	0.12			
D																	D		
J	N	OTE:		DIMENSION CIFIED.	IS ARE IN INCHES U	JNLESS C	THERWISE												
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE								<u>D</u>										
	ON CODE WIRES AND FLEX/24 STRANDED CABLES.																_		
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".								B										
	M.	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																	
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.														С				
	Beveled wire entry————————————————————————————————————																		
$\rightarrow$	INSTALLATION GUIDE DIE CODE = 42							Wire inspection hole								$\leftarrow$			
		IE COLOR =								8									
															alad				
														) Die Çi	Olor				
В			ւ(Մ	L)us	RoHS				ВС	OLT SIZE—	Color coded barr	el mar	kings	'			В		
			1103		2002/95/EC														
			WIRE CONN ZMVV/2/7/8	EU ECTORS E513813															
																	_		
										HUYA	® CELES	TRA	CO	RPOI	RATIO	NC			
А															ngzhou 511495.				
A										RS AND SOLDERING					Α				
									LUGS FOR CODE AND FLEX CABL						E				
	00	0 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.						IATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	DA1014A-260			TS THE	RID ANGLE PI	ROJECTION	ON				
1	REV	DATE	DWN	CHK	D	ESCRIP <sup>-</sup>			ECN F	ELECTRO TIN PLATE	DWG. NO. 186-cp15	88	nit IN	ICH -	<b>⊕</b> £	$\exists$			
			4			•	3	4	$\overline{A}$	2				1					
								I											