			4				3	7	7	2				•	1		_
•	THE IN	NFORMATION LOSED IN COM	I ON THIS DRA NFIDENCE AN	AWING IS THE D NOT TO BE I	PROERTY OF CELESTRA, IS REPRODUCED, USED OR				CELESTR.			BOLT SIZE	B MIN	C	H ±0.01	D ±0.015	<u> </u>
			FOR WHICH						DA1056A-2		FLEX 275/24 1/0 Weld	5/16	0.78	±0.04			1
														1	1	1	1
D	l	IOTE	4 411	DIMENIOLON		F0 IN F00	OTHERWISE										D
	l N	IOTE:		. DIMENSION ECIFIED.	IS ARE IN INCH	ES UNLESS	OTHERWISE						D)_			
			2. ALL	DA.DB.LA.L	B.WP AND J SE	RIES OF CA	T.NO.S ARE						,				
			2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND ELEXICA STRANDED CARLES														
	-	ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.															
		WITH "P".															
	M	MATERIAL:	HIG	H CONDUCT	TIVITY WROUGI	HT COPPER											
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE							Reveled wire entry — H								l _c	
C		SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.						Beveled wire entry — H									
			001	11/10/11/11		V OIL V LIV.											
										∕—Wire i	nspection hole						
_		INICTALL ATION CLUBS															
→	INSTALLATION GUIDE DIE CODE = 42						$-\left(\left(-\right) - \left(-\right)\right) + c$										
	D	DIE COLOR :	= Pink							4	<u> </u>			Die	Color		
														/_			
			_		,				ВС	OLT SIZE—	Color coded bar	el mar	kings		1		
В			, (U		_ 🗸												В
			C		ROHS 2002/95/EC												
			LIS	TED													
			WIRE CON ZMVV/2/7/	NECTORS 8.E513913													
																	_
			1														
										HUYA	® CELES						
										www.huyaco.com							
٨																	1,
Α		WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE							RING	j	A						
	00	23-Aug-25	Ruby Feng	Feng Sinia Qiu Celestra Standards Spec. Initialed.					MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE WROUGHT COPPER DA1056A-251 NTS							PROJECTION	1
	REV		DWN	СНК		DESCRI	PTION		ECN F	ELECTRO TIN PLATE	DWG. NO. 186-cp15	93	NIT	ICH			
	4 3						Δ		2	· · ·	$\overline{}$,	1		'	
												I					