		Л		1	3	$\downarrow$	7	2		1		1			
				PROERTY OF CELESTR	A, IS	V	CELESTRA	WIRE	SIZE	BOLT	В	C	н	D	
	DISCLOSED IN O DISLOSED EXC			REPRODUCED, USED O	R		CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.01	±0.015	
							LA1038A	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0254	3/8	0.93	0.75	0.40	0.13	
D	NOTE:			IS ARE IN INCHES U	INLESS OTHERWISE										D
		2. ALL LIST	DA,DB,LA,L TED BY "UNI	B,WP AND J SERIES DERWRITERS INC." S AND FLEX/24 STR	AND "CSA" FOR USE										
		OTH			FEEP HOLE UNLESS FFIX OF THE CAT.NO.		B								
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER						<u>9</u> 0								
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry												С		
$\rightarrow$	INSTALLATION GUIDE DIE CODE = 42 DIE COLOR = Pink						Wire inspection hole								$\bigtriangledown$
В	B BOLT SIZE Color coded barre										kings -				В
							HUYA®   CELESTRA CORPORATION     Www.huyaco.com   76. Huancun Rd. Zhongcun Town.     Panyu Dist. Guangzhou 511495.								
A							TITLE WIRE CONNECTORS AND SOLDERING A   LUGS FOR CODE AND FLEX CABLE A								
	00 23-Aug-	25 Ruby Feng	Sinia Qiu	Celestra	Standards Spec. Initialed.		MA	TERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	PRT. NO. LA1038A	SC	CALE NT		RID ANGLE PF	ROJECTION	
	REV DATE	DWN	СНК	DE	ESCRIPTION		ECN FIN		DWG. NO. 186-cp16	07 UN	NIT IN(		ŒE		
		4			3	4		2				1			