		4		3	\downarrow	2			1		
ı	DISCLOSED IN CO	I ON THIS DRAWING IS THE P NFIDENCE AND NOT TO BE RE T FOR WHICH FURNISHED.		5	CELEST CAT.N	101	FLEX	BOLT B SIZE MIN	C ±0.04	H D ±0.01 ±0.015	
					LA1010A	-250 1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0254	#10 0.56	0.76	0.39 0.12	
D	NOTE:	ALL DIMENSIONS SPECIFIED.						D			
			,WP AND J SERIES OF ERWRITERS INC." ANI AND FLEX/24 STRAN	D "CSA" FOR USE		D					
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".										
	MATERIAL:		VITY WROUGHT COP		90° 2						
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry H									С	
	INSTALLATION GUIDE DIE CODE = 42 DIE COLOR = Pink					Wire inspection hole					
В	CUL US ROHS					BOLT SIZE Color coded barrel markings					
		WIRE CONNECTORS ZMVV/2/7/8.E513B13									_
						HUYA www.huyaco.com	76. Hua	TRA CO ncun Rd. Z ist. Guang	hongcun	Town.	
А						WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE					
	00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER LA1010A-250 SCALE NTS FCN FINISH THRID ANGLE PROJUCTION OF THE PROJUCT OF THE PROJU					ī
	REV DATE	DWN CHK	DESC	CRIPTION 3	ECN	ELECTRO TIN PLATE	DWG. NO. 186-cp160	9 UNIT IN	исн С 1]
		Т	I	J	4	~		I	'		