			Л		I		3		7	2		I		1			
I					PROERTY OF C		5	¥	CELESTRA		E SIZE	I BOLT	В	C	Н	D	
			FIDENCE AND		REPRODUCED, l	JSED OR			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.01	±0.015	
							-		LA1038A-25	50 1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0254	3/8	0.83	0.76	0.39	0.12	
D	N	OTE:	SPE	CIFIED.	IS ARE IN INC B,WP AND J S							D				D	
			LIST	ED BY "UNI	DERWRITERS	INC." AND "C	SA" FOR USE										
			OTH				HOLE UNLESS F THE CAT.NO.					B S					
	M	ATERIAL:	HIGH	H CONDUC		GHT COPPER						ogo 🏹					
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry													С			
\rightarrow	INSTALLATION GUIDE DIE CODE = 42 DIE COLOR = Pink								Wire inspection hole								
В	BOLT SIZE Color coded barrel markings													В			
	-																
A									HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495. TITLE WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								
																	A
	00	23-Aug-25	Ruby Feng	Sinia Qiu	Ce	elestra Standar	ds Spec. Initialed.			ATERIAL HIGH-CONDUCTIVIT WROUGHT COPPER	LA1038A-250		CALE NT	IS THR		OJECTION	
I	REV	DATE	DWN	СНК		DESCRI			ECN FI	ELECTRO TIN PLATE	DWG. NO. 186-cp16	11	NIT IN	СН	Ф E		I
			4				3	4	7	2				1			