								- 1									
		4 3				<u>V</u> 2			1					_			
'	THE IN	VFORMATION	ON THIS DRA	WING IS THE	PROERTY OF CELEST REPRODUCED, USED	RA, IS			CELESTRA			BOLT	В	С	Н	D] '
			FOR WHICH		NEI NOBOCEB, OSEB	OIT			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.01	±0.015	-
									LA1012AP-26	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0254	1/2	1.08	0.83	0.39	0.12	
D								,			•				•		D
D	N	IOTE:		DIMENSION CIFIED.	IS ARE IN INCHES	UNLESS	OTHERWISE										
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE																
	ON CODE WIRES AND FLEX/24 STRANDED CABLES.																
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".								B &								
	M	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER															
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE														С		
C					TE PER MIL - T -160 D.WITH "SP" FOR S												~
	1								Bev	Beveled wire entry—/							
\rightarrow	INSTALLATION GUIDE							Wire inspection hole								4	
		DIE CODE = DIE COLOR =									<u> </u>						7
) C						
														Die ¢	olor		
В					V				BO	LT SIZE	Color coded barr	el mar	kings				В
			c (JU S	RoHS 2002/95/EC				ВО	LI OIZL							
			LIST	ΓED													
			WIRE CONF ZMVV/2/7/8	ECTORS .E513913													
	-																
		I	1								051 50			DD 0:	D A = :	21:	
									+	HUYA	R CELES						
										www.huyaco.cor	_						
Α									TITLE WIRE CONNECTORS AND SOLDERING							Α	
								LUGS FOR CODE AND FLEX CABLE									
	00	23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					ds Spec Initialed		MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PRO						ROJECTION		
	REV	DATE	DWN	CHK		DESCRIF			ECN FII	WROUGHT COPPER NISH ELECTRO TIN PLATE	DWG. NO. 186-cp16		NIT	ICH -	()	\exists	
		I	4				3	1		2	.55 5610	-	111	1		_	'
					ı			7	_			ı					