									l									
			4				3		7		2				1			
1		THE INFORMATION ON THIS DRAWING IS THE PR DISCLOSED IN CONFIDENCE AND NOT TO BE RE						CELESTF				BOLT		С	Н	D	1 '	
				FURNISHED.	KEFRODOCED, C	JOED ON			CAT.NC			FLEX	SIZE 1/4	MIN	±0.04	±0.01	±0.015	ł
									LA1014AP-	251 1/0 AV	VG	275/24 1/0 Weld	1/4	0.80	0.85	0.45	0.13	ł
D																		D
	N	IOTE:			S ARE IN INC	HES UNLESS	S OTHERWISE							D				
				ECIFIED.								1		, ,	-			
		2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE																
		ON CODE WIRES AND FLEX/24 STRANDED CABLES.																
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.																
		WITH "P".							95									
	M	IATERIAL:	HIC	SH CONDUCT	IVITY WROUG	HT COPPER	?											
С	F	INISH:			LATE UNLESS E PER MIL - T		E		Be	eveled wire en	trv —	/ -> <del>      -</del>						С
					.WITH "SP" FC				Β.	overed wite en	cı y							
											Wire ir	spection hole						
_	INSTALLATION GUIDE																	
	DIE CODE = 42								$\begin{array}{c c} \begin{pmatrix} & & \\ &$									
	D	IE COLOR =	= Pink								$\perp$				Die ¢	Color		
											/ '				/ <b>L</b>			
									BOLT SIZE — Color coded barrel markings —									
В				,														В
		c(	(Jr) <sup>ns</sup>	RoHS.														
			ICTED	2002/95/EC														
			E CONNECTORS															
											<b>/</b>	® CELES	TRA	CO	RPO	RATI	ON	
										HU		76. Hua	incun	Rd. ZI	nongci	un Tov	/n.	
				+						www.huya	co.cor	n Panyu [	Dist. G	uangz	zhou 5	11495		
Α		TITLE WIRE CONNECTO							NECTORS	RS AND SOLDERING					A			
		LUGS FOR CODE AND FLEX CABLE																
		MATERIAL HIGH COMP													ROJECTION	)N		
				+	Ce		rds Spec. Initiale	ed.	$\perp$	WROUGHT		LA1014AP-251		N	TS	(h)		
ı	REV	DATE	DWN	CHK		DESCR		,	ECN	ELECTRO TI	N PLATE	186-cp16	21   "	IV.	ICH	Ψ'		1
	_ 4   3							_	_	2					1			
									I									