			4				3		<u> </u>	2					1		_
•	THE IN	NFORMATION OSED IN COM	I ON THIS DRA NFIDENCE AN	AWING IS THE D NOT TO BE I	PROERTY OF CEI REPRODUCED, US	LESTRA, IS SED OR			CELESTR CAT.NO	* * _	E SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	H ±0.01	D ±0.015	
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.					DA2034A-2		325/24 2/0 Weld	3/4	1.52	0.96		0.13	1
										<b>'</b>	1						1
D	<b> </b>	IOTE:	4 411	DIMENSION			OTHERWISE										D
	l <sup>in</sup>	IOTE:		CIFIED.	S ARE IN INCH	IES UNLESS	OTHERWISE						Д	)			
			2. ALL	DA,DB,LA,L	B,WP AND J SE	ERIES OF CA	T.NO.S ARE						1——				
					ERWRITERS I												
		ON CODE WIRES AND FLEX/24 STRANDED CABLES.  PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.										_					
			WIT	H "P".								00					
	М	MATERIAL:	HIG	H CONDUCT	IVITY WROUG	HT COPPER	!										
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.						Beveled wire entry————————————————————————————————————								С		
					.WITH "SP" FO				В	eveled wife entry							
									Wire inspection hole								
$\rightarrow$	IN	INSTALLATION GUIDE															4
	DIE CODE = 45 DIE COLOR = Black					() - \frac{\frac{1}{8}}{8} (\frac{1}{8})											
		AL OOLON.	- Diack								<u> </u>			Die	Color I		
									_	017.0175	Color coded barr	ol mai	rkinge	/=			
ь					./				В	OLT SIZE—	Color coded barr	Cillia	Kiilys				
В			c(N	L)us	RoHS												В
			110.		2002/95/EC												
			WIRE CON ZMVV/2/7/	IEU NECTORS 8 E513913													
											R CELES	TDA	CO	DD0	DΛT	ON	1
									+-	HUYA	76. Hua						
									+	www.huyaco.co							
Α		WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE							LDF	RING	NG A						
		00.4 55	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE						TH		PROJECTION						
	00 REV	DATE	Ruby Feng	Sinia Qiu CHK	Cele	estra Standar DESCRII	rds Spec. Initiale	a.		WROUGHT COPPER	DA2034A-251	-	NIT	TS		$\Box$	
	KEV	DATE		CHK	1	DESCRI		/	N ECIV	ELECTRO TIN PLATE	186-cp16	47	11	1CH	Ψ		]
			4		I		3	_		2		1			ı		