		4		I	3	$\downarrow$	7	2		I		1			
	THE INFORMATIC	•	WING IS THE F	PROERTY OF CELESTRA		V	CELESTRA	Z WIRE	SIZE	I BOLT	В	C I	н	D	1
		INFIDENCE AND	) NOT TO BE F	REPRODUCED, USED OF			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.01	-	5
D	DISLOSED EXCE		URNISHED.				DA3056A	3/0 AWG	150 Navy 2/0 Weld 325/24 = 131 kcmil 133/.0316 259/.0227 427/.0177	5/16	0.88	0.92	0.51	0.13	D
	NOTE:		DIMENSION CIFIED.	S ARE IN INCHES UI	NLESS OTHERWISE			·	•				•		1
		LIST	ED BY "UND	3,WP AND J SERIES ERWRITERS INC." A S AND FLEX/24 STR/	ND "CSA" FOR USE	D									
		OTH		).WITH "L" HAS NOT ECIFIED IN THE SUF											
	MATERIAL:	HIGH	H CONDUCT	IVITY WROUGHT CC	PPER	B SS									
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.												С		
	Beveled wire entry — H														
•						·								1	
$\rightarrow$	INSTALLATION GUIDE DIE CODE = 50														
	DIE COLOR = Orange						Wire inspection hole								
В				RoHS 2002/95/EC		BOLT SIZE Color coded barrel markings									
								HUYA	R CELES 76. Hua Panyu I	ancun	Rd. Zh	nongcu	in Tow		
A					Image: Wire connectors and soldering A   LUGS FOR CODE AND FLEX CABLE A										
	00 23-Aug-28	6 Ruby Feng	Sinia Qiu	Celestra S	standards Spec. Initial	led.	MAT	FERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	PRT. NO. DA3056A	SC	CALE NT	THR	ID ANGLE PF	ROJECTION	-
	REV DATE	DWN	СНК		SCRIPTION		ECN FINI		DWG. NO. 186-cp16	77 <sup>UI</sup>	NIT.	СН	ŒE	$\square$	
	· ·	4			3	4		2			-	1			