		4			3	+	2		1	1			
	THE INFORMATION OF THE INFORMATI	ONFIDENCE AND	O NOT TO BE REPRO	RTY OF CELESTRA, IS DDUCED, USED OR		CELES CAT.		IRE SIZE FLEX	-	B C	H ±0.01 ±	D :0.015	
D	DISLOSED EXCE	PT FOR WHICH	FURNISHED.			DA3056	A-250 3/0 AWG	150 Navy 2/0 Weld 325/24 = 131 kcmil 133/.0316 259/.0227 427/.0177	5/16 0.	78 0.96	0.51	0.13	
	NOTE:		DIMENSIONS AR CIFIED.	E IN INCHES UNLES	SS OTHERWISE								
_	2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.  D												
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".												
С	MATERIAL FINISH:	ELE: SPE	CTOR-TIN PLATE CIFED PLATE PE	WROUGHT COPPE UNLESS OTHERWI R MIL - T -16366.					90° *t3			С	
	SUFFIX CAT.NO.WITH "SP" FOR SILVER.  Beveled wire entry												
$\rightarrow$	INSTALLA DIE CODE DIE COLO						Wire inspection hole						
В	BOLT SIZE Color coded barrel markings										В		
-		ZMVV/2//8_E513913										-	
							HUY www.huyaco.	<b>7</b> 6. Hua	ncun Rd.	ORPOF Zhongcu ngzhou 5	ın Town		
Α							WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE						
		5 Ruby Feng			ards Spec. Initialed.		MATERIAL HIGH-CONDUCTI WROUGHT COPF	DA3056A-250	SCALE	NTS	ID ANGLE PRO	JECTION	
	REV DATE	DWN 4	CHK	DESCI	3	ECN	ELECTRO TIN PLA	TE 186-cp16	81   0111	INCH 1	Ψ <u></u>		