			4				3	\downarrow	7		2				1				
1	DISCL	OSED IN CON		D NOT TO BE F	PROERTY OF CELES REPRODUCED, USEE				CELESTR CAT.NO		WIRE CODE	SIZE FLEX	BOLT SIZE		C ±0.04	H ±0.01	D ±0.015	;	
	DIOLO			I OINNOHED.				[DA3010A-2	251	3/0 AWG	450/24 3/0 Wel	d #10	0.54	1.06	0.57	0.14]	
D																		D	
D	N	IOTE:		DIMENSION	IS ARE IN INCHES	S UNLESS C	DTHERWISE							D					
			2. ALL	DA,DB,LA,LI	B,WP AND J SERI										-				
				DERWRITERS INC S AND FLEX/24 S															
			OTH		D.WITH "L" HAS N ECIFIED IN THE \$				and the second sec										
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																		
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.								Beveled wire entry — H									
										/—Wire ir	nspection hole								
\rightarrow	> INSTALLATION GUIDE																	\leftarrow	
F	DIE CODE = 50 DIE COLOR = Orange																		
	BOLT SIZE Color coded barrel markings																		
В			ູດ						D					0				в	
					2002/95/EC														
			WIRE CON ZMVV/2/7/8																
											IUYA	® CELI	ESTR/					1	
									<u> </u>		w.huyaco.cor		uancun u Dist. (
А									TITLE WIRE CONNECTORS AND SOLDERING									A	
									LUGS FOR CODE AND FLEX CABLE										
			Ruby Feng	<u>├───</u> ┟			s Spec. Initialed	J.		MATERIA FINISH	L HIGH-CONDUCTIVITY WROUGHT COPPER	DA3010A-2	51	LINIT	TS				
	REV	DATE	DWN	СНК	1	DESCRIP	TION 3	1	ECN		ELECTRO TIN PLATE	186-cr	1688	IN	ICH	ΨĽ]	
			4		I		3	4	7		2				I				