	•								_								
			4				3			2					1		,
	DISCL	OSED IN CO	VFIDENCE ANI	D NOT TO BE F	PROERTY OF CELESTF REPRODUCED, USED C	RA, IS DR			CELESTR CAT.NO		SIZE FLEX	BOLT SIZE	B MIN	±0.04	H ±0.01	D ±0.015	
	DISLO	SED EXCEPT	T FOR WHICH	FURNISHED.					DA3056A-2		450/24 3/0 Weld	5/16	0.79	1.06		0.14	İ
D																	D
D	N	IOTE:	1. ALL	DIMENSION	S ARE IN INCHES U	JNLESS C	THERWISE						_				
			SPE	CIFIED.							I	ı	D	-			
					B,WP AND J SERIES												
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.															
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS																
	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																
	I M	IATERIAL:			IVITY WROUGHT C	OPPER						9)					
_																	
С		FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.							Beveled wire entry H								С
			SUF	FIX CAT.NO	.WITH "SP" FOR SIL	VEK.											
									—Wire inspection hole								
_		INICTALL ATION CUIDS															_
	INSTALLATION GUIDE DIE CODE = 50														\leftarrow		
	D	IE COLOR :	= Orange								,			Die	Color		
														/=			
_					. /				В	OLT SIZE—	Color coded bar	el ma	rkings				_
В			ւ(Ո	L)us	RoHS												В
			0	ン。 ご	2002/95/EC												
			LIS WIRE CONI ZMVV/2/7/8														
	1																
											R CELES	TRA	CO	RPO	RATI	ON	
										HUYA	76. Hua	ncun	Rd. Zl	nongc	un Tov	vn.	
_						_			_	www.huyaco.coi	m Panyu I	Dist. G	uangz	zhou 5	511495		
Α	TITLE WIRE CONNECTORS AND SO						LDE	DERING A									
		LUGS FOR CODE AND FLEX CABLE						.E									
	00	23-Aug-25	Ruby Feng	Sinia Qiu	Celestra	Standards	Spec. Initialed.			MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	PRT. NO. DA3056A-251	S	CALE N	TS TH	IRID ANGLE F	PROJECTION	
ı	REV		DWN	СНК	DI	ESCRIP	TION		ECN	FINISH ELECTRO TIN PLATE	DWG. NO. 186-cp16	90	NIIT	ICH	1		
	4 3						Δ		2					1		'	
	_ '											1					