			4			3	\downarrow	7	2					1			
1	DISCL	OSED IN CON		D NOT TO BE	PROERTY OF CELEST REPRODUCED, USED (CELESTR/ CAT.NO		WIRE SIZE	FLEX	BOLT SIZE	B MIN	C ±0.04	H ±0.01	D ±0.015	
							[DA3010A-20	61 3/0 AWG	450/	24/ 3/0 Weld	#10	0.52	1.03	0.56	0.14	
D																	D
U	N	IOTE:		DIMENSION	IS ARE IN INCHES U	JNLESS OTHERWISE							D				
						S OF CAT.NO.S ARE AND "CSA" FOR USE											
					S AND FLEX/24 STF												
			OTH	IERWISE SF		T PEEP HOLE UNLESS IFFIX OF THE CAT.NO.				,	E	_ ۲	/				
	N	1ATERIAL:		H "P". H CONDUCI	IVITY WROUGHT C	OPPER						20					
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.							Beveled wire entry — H								
					WITH "SP" FOR SIL				,								
								Wire inspection hole									
\rightarrow	D	NSTALLATIO	50													\leftarrow	
	D	IE COLOR =	= Orange							μ_	V				or		
								BC		Color	coded barr	el marl	kings –				
В			c(U	Dus	,RoHS,												В
			LIST	FED	2002/95/EC												
			WIRE CON ZMVV/2/7/8														
									HUY	R	76. Hua						
•								+	www.huyaco	.com	Panyu E						
A								TITLE WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									A
	00	00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.						MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECT								OJECTION	·
	REV	DATE	DWN	CHK		ESCRIPTION	~ .	ECN F	ELECTRO TIN P	DWG N		97 ^{UN}			Ф E	\square	
			4			3	4		2					1			
							1										